arXiv:submit/8411944 [cs.AI] 23 Nov 2026

Context-Grounded Skill Internalization for Vision-Language Agents

Jinlin Liu[1,2] Yumeng He[1,3] Qihan Huang[1,*] Kevin Qinghong Lin[4,†] Han Peng[1,†]

[1]Ant Group [2]The University of Hong Kong [3]Shanghai Jiao Tong University [4]University of Oxford

[*]Project lead. [†]Corresponding authors.

Abstract

*Skill internalization offers a way for agents to learn useful behaviors from skills and use them without explicit guidance in context at inference time. A common approach is to generate demonstration trajectories with the skill in context and then fine-tune the same model on its own trajectories with the skill removed. However, this leads to the problem that the model may learn to reference the removed skill, which we named as context misalignment (*CoMi*). In this work, we first analyze agent behaviors related to* CoMi *under this common pipeline. Across ALFWorld [33], WebShop [44], and ARC-AGI-1 [7], skill-removed fine-tuning consistently results in* CoMi*: 12.2–46.0% of test trajectories reference the removed skill. To address this problem, we develop Context-Grounded Skill Internalization (CGSI). CGSI uses a sentence detector to identify unsupported references and then masks or rewrites the selected sentences before fine-tuning. Experimental results demonstrate the effectiveness of CGSI and reveal two key findings. (i) Compared with directly fine-tuning with the skill removed, CGSI reduces* CoMi *at test time by 72.5–94.6% while preserving task success. (ii) Compared with existing reinforcement learning-based skill-internalization baselines, CGSI achieves comparable performance with substantially less training time. CGSI also significantly reduces processing costs compared with large-scale trajectory auditing and correction.*

1. Introduction

AI agents are increasingly used for real-world work, such as resolving software issues and operating graphical interfaces [21, 41, 47, 48]. Such work often requires specialized procedures and domain knowledge that a general-purpose model may lack. Agent products such as Claude Code supply this knowledge through *skills*, which package instructions, scripts, and resources and are loaded into the agent's context when a task needs them [23, 43, 49]. Skills are therefore a test-time augmentation, and their benefit lasts as long as the skill stays in the context. Skill internalization removes the test-time dependence on the skill by moving the skill's guidance into the model weights, so that the agent exhibits the behavior the skill introduced without loading the skill into its context [25, 40].



Figure 1. **Context misalignment.** (1) A successful ARC response, sampled with the skill, references guidance that is present. (2) SFT trains on the same response with the skill removed, so the referenced guidance is absent.

A common way to internalize a skill is to generate demonstration trajectories with the skill in context using the model itself, and then fine-tune the same model on them with the skill removed. Llama 2-Chat follows this recipe for safety. It generates responses under a safety preprompt and is fine-tuned on its own responses without the preprompt [36]. SELF-ALIGN fine-tunes LLaMA on its own principle-guided responses with the principles removed [35], and agent training applies the same recipe to retrieved hints and reflection skills [9, 18]. This recipe is a supervised

fine-tuning (SFT) form of *context distillation* [2, 34]. It changes the training input but keeps the supervision target, so the model learns to reproduce what it wrote with the skill. However, a target written with the skill can depend on it. Demonstration trajectories can contain statements that reference the skill, and these statements remain training targets after the skill is removed. Figure 1 shows an example from ARC [7]. A skill-guided agent plans to execute and verify its inferred rule with a script, solve.py, and explains, "The solve.py file doesn't exist. According to the task guidance, I need to create it." The trajectory carries two things into training, a useful strategy and a reference to the skill that supplied it. Once the skill is removed from the SFT input, training rewards the model for referencing guidance it cannot see. We call this *context misalignment* (CoMi), in which an output references a source absent from its visible context.

We conduct a comprehensive analysis of this problem. After skill removal, CoMi appears in 18.3–75.4% of successful teacher trajectories across ALFWorld [33], WebShop [44], and ARC-AGI-1 [7]. This behavior can be carried over to the trained models. After fine-tuning on these trajectories with the skill removed, the models exhibit CoMi in 12.2–46.0% of test trajectories.

To solve this, we introduce **Context-Grounded Skill Internalization (CGSI)**. The core of CGSI is a sentence detector that identifies sentences containing unsupported references after skill removal. We then rewrite or mask the loss on these sentences before fine-tuning without the skill.

We evaluate CGSI on ALFWorld [33], WebShop [44], and ARC-AGI-1 [7] with the vision-language models (VLMs) Qwen3.5-4B and Qwen3.5-9B [28]. Under full-parameter SFT, its masking version reduces CoMi by 72.5–94.6% relative to direct fine-tuning while preserving task success. For example, with Qwen3.5-4B on WebShop, CoMi falls from 46.0% to 3.4% without loss of task success. CGSI also substantially reduces the cost of trajectory auditing and correction. On ARC, its rewriting version reduces the API cost of processing 2,281 trajectories from about $1,378 to $165. With Qwen3.5-4B on ALFWorld, CGSI reaches 85.0% success in 1.25 training hours, compared with 81.0% for Skill0 [25] in 19.1 hours.

Our contributions are:

- To the best of our knowledge, we are the first to define and systematically study context misalignment (CoMi) in skill internalization. We show that CoMi is **common in successful demonstration trajectories** and **can be carried into trained models**.
- To solve this, we propose CGSI to **correct training supervision** that loses context support after skill removal, using a sentence detector to select sentences for loss masking or rewriting before fine-tuning.
- Experiments demonstrate the improvement. CGSI **reduces CoMi by 72.5–94.6%** at a low cost while **preserving the task success** of the fine-tuned model.

2. Related Work

Agent training. By interleaving reasoning with tool calls and environment feedback [45], agents complete multi-step tasks in simulated homes [33], online stores [44], software projects [41], and open-world games [39]. Beyond prompting, these agents are improved by post-training, which learns from demonstrations, human preferences [27], or a teacher's outputs [1, 13]. For agents, SFT on interaction trajectories improves performance on the trained tasks [4] , while reinforcement learning (RL) methods such as GRPO optimize the policy directly using task-outcome rewards [31].

Agent skills. Skills package reusable procedures, knowledge, and experience that an agent can draw on across tasks [39, 50]. Since such skills must be provided at test time, recent work attempts to move them into the model weights. SFT-based internalization generates trajectories with the guidance and fine-tunes on them without it [9, 18, 46]; the same idea underlies context distillation [2, 34–36] and, more broadly, learning with privileged information [5, 15, 24, 38]. Other approaches use RL or self-distillation. Skill0 progressively withdraws skills during RL [25]. DGO optimizes the policy using trajectories collected with guidance from an experience bank [3]. Self-distillation methods give the teacher privileged context, such as skills [40] or reference solutions [51]. Recent work has also begun to address context-dependent traces in training trajectories. Harness-Zero masks reviewer-perspective reasoning by keyword matching [46], and DGO rewrites experience-dependent trajectories [3]. Both treat these traces as a data-cleaning step within their own pipelines. We study CoMi as a distinct problem and measure it in both demonstration trajectories and trained models.

Hallucination and faithfulness. Hallucination research asks whether generated statements are supported by the source or the available evidence [26, 29], as unsupported statements undermine the reliability of model outputs and the trust users place in them [17, 20]. Faithfulness research asks whether stated reasoning reflects how the model actually reached its answer [19]; chain-of-thought can be unfaithful to the factors that drove an answer [22, 37], misleading users about why a model behaves as it does. An agent with CoMi references guidance absent from its visible context and misstates the basis for its actions. This makes the agent harder to audit, because users and overseers rely on its stated reasoning and referenced sources to verify and monitor its behavior [6, 11]. Moreover, CoMi may hurt instruction following, since a model that recalls rules absent from its



Figure 2. **CGSI: detector training and context-aligned SFT.** *(a) Detector training (top):* Step 1 obtains paired sentence labels from VLM audits; Step 2 extracts sentence-level features from a frozen backbone, combining log-probability differences between the two contexts with hidden-state representations; Step 3 fits a logistic classifier to these features and labels. The resulting detector is calibrated and frozen. *(b) Context-aligned SFT (bottom):* Skill-guided demonstration trajectories are scored by the frozen detector. Selected sentences are loss-masked or rewritten, and the model is trained without the skill.

context can keep acting on them when its visible instructions ask for something different [30].

3. Context Misalignment under Skill Removal

3.1. Interaction and training context

An agent receives a prompt p containing the system instructions, tool specification, and task. At turn k, it produces reasoning and an action as $y^{(k)}$; the environment returns observation o_k. Let $\tau = (o_0, y^{(1)}, o_1, \ldots, y^{(K)}, o_K)$ and let $\tau_{<k}$ be its history before turn k, serialized according to the agent's interaction protocol. A skill s adds procedural guidance to the prompt. The two contexts differ only in s:

$$c_k^+ = (p, s, \tau_{<k}), \qquad c_k^- = (p, \tau_{<k}). \tag{1}$$

A frozen sampling policy generates $y^{(k)} \sim \pi_{\theta_0}(\cdot \mid c_k^+)$, and successful trajectories form the SFT set $\mathcal{D}$. At test time, the agent receives only c_k^-.

3.2. Context misalignment and paired labels

A statement is context-misaligned when it explicitly references guidance or another source that does not appear, literally or in equivalent form, in its visible context. "I should open the container" is a plan; "According to the provided guide, I should open the container" also references a source, and becomes CoMi when no guide is visible. CoMi concerns references only: a wrong action is not CoMi.

Split reasoning into sentences $u_{k,j} = y^{(k)}_{\ell_{k,j}:r_{k,j}}$, where $\ell_{k,j}$ and $r_{k,j}$ are the start and end character offsets of sentence j in turn k. An auditor $\mathcal{A}(u; c) \in \{0, 1\}$ marks unsupported references in a sentence under context c. For the same output and history, the paired label is

$$b_{k,j} = \mathcal{A}(u_{k,j}; c_k^-)\,[1 - \mathcal{A}(u_{k,j}; c_k^+)]. \tag{2}$$

Thus $b_{k,j} = 1$ marks references that are supported with the skill and unsupported after its removal; references already unsupported under c_k^+ are excluded, so the label isolates the effect of removal. We implement $\mathcal{A}$ with two independent calls to a frozen VLM auditor, Kimi-K2.7-Code, and resolve

Table 1. **CoMi introduced by skill removal in successful teacher trajectories:** CoMi (%), with positive / total trajectories in parentheses. A positive trajectory contains at least one reference that loses context support.

Model	ALFWorld	WebShop	ARC-AGI-1
4B	33.97 (412 / 1,213)	64.79 (322 / 497)	43.95 (552 / 1,256)
9B	40.28 (518 / 1,286)	18.34 (104 / 567)	75.45 (1,721 / 2,281)

disagreements with a third call. For sentences with several references, we check the individual fragments before mapping them to sentences. At deployment, the agent receives no skill; we therefore audit its test outputs only in the skill-free context. Supp. B details the audit and its validation.

3.3. SFT objectives with and without the skill

We consider two SFT settings: SFT (skill kept) retains the skill in the training input, whereas SFT (skill dropped) removes it. Let $y_t^{(k)}$ be a target token, $y_{<t}^{(k)}$ its within-turn prefix, and $T = \sum_k T_k$ the number of model target tokens in a trajectory. Observations enter as context. For context choice c and token weights w, write

$$\mathcal{L}(\theta; c, w) = -\frac{1}{T} \sum_{k=1}^{K} \sum_{t=1}^{T_k} w_{k,t} \log \pi_\theta(y_t^{(k)} \mid c_k, y_{<t}^{(k)}). \quad (3)$$

The corresponding objectives are $\mathcal{L}_{\text{Keep}} = \mathcal{L}(\theta; c^+, \mathbf{1})$ and $\mathcal{L}_{\text{Drop}} = \mathcal{L}(\theta; c^-, \mathbf{1})$.

3.4. Misalignment in successful demonstration trajectories

Table 1 shows that successful demonstration trajectories frequently contain references that lose support after skill removal, from 18.3% on WebShop-9B to 75.4% on ARC-9B. Model size does not predict the rate: the 9B teacher produces fewer such references than 4B on WebShop (18.3% versus 64.8%) but more on ALFWorld and ARC. A natural fix is to ask the teacher not to mention the skill. This makes the problem worse: on 1,000 ALFWorld tasks, removal-induced CoMi rises from 38.9% to 51.9%. Some outputs now reference the prohibition itself: "The system instructions say not to mention the skill or its contents in thinking." This reference is supported during rollout but loses its source when the skill-related instructions are removed before SFT; prompt-level prevention is analyzed in Supp. F.

4. Context-Grounded Skill Internalization

VLM auditing is expensive: on ARC, scanning a successful demonstration trajectory costs at least 1.13–1.14M tokens on average, and auditing the 2,281 ARC-9B training demonstration trajectories with a VLM costs about $1,200 at list price. CGSI places the audit between skill-guided generation and skill-free SFT and performs it with a detector using two signals: how much a sentence depends on the skill, and what it says. The detector is developed once (Fig. 2(a), Steps 1–3) and then reused frozen in context-aligned SFT (Fig. 2(b)).

4.1. Likelihood differences reveal skill dependence

A sentence that references the skill should be easier to predict when the skill is visible, and harder once it is removed. Using the initial agent model $q = \pi_{\theta_0}$, kept frozen, we compare each target token under the two contexts with an identical output prefix:

$$\begin{aligned} \Delta_{k,t} = \; & \log q(y_t^{(k)} \mid c_k^+, y_{<t}^{(k)}) \\ & - \log q(y_t^{(k)} \mid c_k^-, y_{<t}^{(k)}). \end{aligned} \quad (4)$$

Let $I_{k,j}$ be the set of positions t of the target tokens in turn k that fall within sentence $u_{k,j}$; we summarize the sentence's overall and local dependence as

$$\begin{aligned} g_{k,j}^{\text{mean}} &= \frac{1}{|I_{k,j}|} \sum_{t \in I_{k,j}} \Delta_{k,t}, \\ g_{k,j}^{\text{peak4}} &= \max_{W \in \mathcal{W}_{k,j}} \frac{1}{|W|} \sum_{t \in W} \Delta_{k,t}, \end{aligned} \quad (5)$$

where $\mathcal{W}_{k,j}$ contains consecutive windows of $\min(4, |I_{k,j}|)$ tokens. The peak feature captures a short dependent phrase, such as "according to the skill," inside a longer sentence.

4.2. Hidden states distinguish references from plans

Skill dependence alone does not identify CoMi, because the skill also makes valid plans more likely. "I should check the container" and "According to the skill, I should check the container" may both have positive gaps, yet only the second references the skill. To capture what a sentence says, we pool last-layer hidden states $\mathbf{h}_{k,t}^-$ under the skill-free context:

$$\begin{aligned} \bar{\mathbf{h}}_{k,j} &= \frac{1}{|I_{k,j}|} \sum_{t \in I_{k,j}} \mathbf{h}_{k,t}^-, \qquad \mathbf{e}_{k,j} = \frac{\bar{\mathbf{h}}_{k,j}}{\|\bar{\mathbf{h}}_{k,j}\|_2}, \\ \mathbf{z}_{k,j} &= \text{Std}\left([\mathbf{e}_{k,j}, g_{k,j}^{\text{mean}}, g_{k,j}^{\text{peak4}}]\right). \end{aligned} \quad (6)$$

The hidden state represents what the sentence says, and the gaps how its likelihood depends on the skill.

4.3. Fitting and calibrating a sentence auditor

After splitting development trajectories by task into fitting, calibration, and held-out sets, a logistic model learns from paired labels b:

$$f_\phi(\mathbf{z}) = \mathbf{v}^\top \mathbf{z} + \beta, \qquad P_\phi(b = 1 \mid \mathbf{z}) = \sigma(f_\phi(\mathbf{z})), \quad (7)$$

using class-balanced cross-entropy and ℓ_2 regularization:

$$\mathcal{L}_{\text{det}} = \frac{1}{|\mathcal{D}_{\text{fit}}|} \sum_{(\mathbf{z},b) \in \mathcal{D}_{\text{fit}}} \text{BCE}_{\text{bal}}\big(b, \sigma(f_\phi(\mathbf{z}))\big) + \frac{\lambda}{2} \|\mathbf{v}\|_2^2. \quad (8)$$

A sentence is selected when its score reaches a threshold η, which we set on the calibration split separately for each benchmark and model. We then freeze ϕ and η and predict $\hat{b}_{k,j} = \mathbf{1}\{f_\phi(\mathbf{z}_{k,j}) \geq \eta\}$ on new demonstration trajectories. Thresholds are in Supp. D.

4.4. Masking selected supervision

Masking stops training the model to produce the selected sentences: a target token is masked when it lies entirely inside a selected sentence. Let $\hat{m}_{k,t} \in \{0, 1\}$ be 1 if target token t of turn k is masked and 0 otherwise. CGSI (Mask) sets the token weights in Eq. (3) to $w_{k,t} = 1 - \hat{m}_{k,t}$:

$$\mathcal{L}_{\text{Mask}} = \mathcal{L}(\theta; c^-, \mathbf{1} - \hat{m}). \tag{9}$$

Masking changes only which tokens are supervised: the normalizer T still counts all target tokens, so the remaining tokens keep their loss scale, and the selected text stays in the teacher-forced prefix, so later reasoning and actions are conditioned exactly as before. Removing the supervision entirely matters: a softer variant that only down-weights the selected sentences leaves more CoMi, as shown in Supp. D.

4.5. Rewriting selected text

CGSI (Rewrite) uses a VLM to rewrite each selected fragment so that it holds without the skill. We then train on the rewritten trajectories without the skill. Rewriting keeps supervision on the corrected text but needs VLM calls; Supp. C gives details.

4.6. A generate–audit–correct–train framework

These steps form a four-stage framework (Fig. 2(b)): a frozen sampling policy generates demonstration trajectories with the skill; the detector marks the sentences that lose support under the skill-free training context; the selected sentences are masked or rewritten; and the model is trained on the corrected demonstration trajectories without the skill. In contrast, the VLM Audit baselines VLM Audit (Rewrite) and VLM Audit (Mask) use a full VLM audit to select sentences for rewriting or loss masking, respectively. The full algorithm is in Supp. C.

5. Experiments

5.1. Setup

Environments and data. ALFWorld [33] covers six types of household tasks, with 274 test tasks; in WebShop [44], the agent searches for and buys a product that matches a shopping instruction, with 500 test tasks; and ARC-AGI-1 [7] requires inferring a grid transformation from a few examples, with 400 evaluation tasks. We run ARC as a multimodal agent task in which the agent sees the grids as an image and can write and run code. The skills provide household procedures, shopping strategies, and grid-transformation guidance, respectively. Each model generates skill-guided demonstration trajectories on 1,920 training tasks for ALFWorld and for WebShop and on 6,360 ARC tasks; for a given model and benchmark, all methods train on the same successful demonstration trajectories. Detectors are developed on separate pools of 673–680 tasks per benchmark. Details are in Supp. H.

Training and evaluation. We train with full-parameter SFT and rank-16 LoRA [16] for three epochs. Unless otherwise specified, all SFT methods use the same skill-guided demonstration trajectories and are evaluated without the skill. Base is the untrained model. SFT (skill kept) retains the skill in the training input, whereas SFT (skill dropped) removes it. CGSI (Mask) and CGSI (Rewrite) mask or rewrite the sentences selected by our detector; they are the two variants of CGSI. VLM Audit (Rewrite) and VLM Audit (Mask) rewrite or mask the sentences selected by a full VLM audit. We also compare with Skill0, Skill-SD, and OPSD on ALFWorld-4B (Tab. 4). Kimi-K2.7-Code performs auditing and rewriting. Each model is evaluated with one rollout per test task.

Success rate (SR) is the percentage of test tasks completed: a WebShop task counts as successful only if it receives the full score of 100, and an ARC task only if every predicted grid matches exactly. For trained models, CoMi is the percentage of test trajectories with at least one unsupported reference, audited without the skill. Humans agree with 255 of 260 sampled audit positives. To check for misses in long trajectories, GPT-6.1 Sol independently re-audits 1,245 Kimi-negative test trajectories. Humans adjudicate the disagreements and confirm five misses. Training settings and metric definitions are in Supp. E and A.

Compute. All experiments in this paper run on NVIDIA H800 GPUs (8 per node), using about 5,832 H800 GPU-hours in total; external VLM calls use about 40.44B tokens in total, about $43,421 at official API prices.

5.2. Capability and alignment after SFT

The SFT baselines trade off task success and CoMi. In Tab. 2, under full-parameter SFT, SFT (skill kept) improves on Base by 27–37 success points on ALFWorld and WebShop. SFT (skill dropped) further improves success by 3.8–8.0 points across all six settings, but raises CoMi from 0–2.2% to 12.2–46.0%. For SFT (skill dropped), CoMi at test time tends to be higher when it is more common in the training demonstrations. The highest test-time rates are on WebShop-4B and ARC-9B (46.0% and 37.25%), which also have the highest rates in the training demonstrations. WebShop-9B has the lowest rate in both. Skill-guided generation also contributes much of the success. On ALFWorld-4B, SFT on 773 successful rollouts sampled without the skill reaches 54.7%, whereas SFT (skill kept) and SFT (skill

Table 2. **Capability and context alignment after SFT.** Success rate (SR) and deployment CoMi in %; WebShop score in $[0, 100]$. All methods train on the same skill-guided trajectories. SFT (skill kept) trains with the skill; the others train without it. CGSI variants use sentences selected by our detector; the VLM Audit baselines use sentences flagged by a full VLM audit. No method receives the skill at test time. Silver-gray text: CoMi; muted red: CoMi $\geq 10\%$. Bold black: best skill-free SR and score within each group.

	ALFWorld													WebShop			ARC-AGI-1	
	Pick (59)		Clean (58)		Heat (39)		Cool (46)		Look (31)		Pick2 (41)		All (274)		500 tasks			400 tasks	
Method	SR ↑	CoMi ↓	SR ↑	CoMi ↓	SR ↑	CoMi ↓	SR ↑	CoMi ↓	SR ↑	CoMi ↓	SR ↑	CoMi ↓	SR ↑	CoMi ↓	SR ↑	Score↑	CoMi ↓	SR ↑	CoMi ↓
Full-parameter · Qwen3.5-4B																			
Base	86.4	1.7	22.4	1.7	5.1	2.6	10.9	0.0	38.7	3.2	61.0	0.0	39.4	1.5	6.8	14.0	0.6	2.00	0.00
SFT (skill kept)	89.8	0.0	81.0	6.9	59.0	0.0	54.3	2.2	83.9	0.0	85.4	0.0	76.3	1.8	35.4	46.1	1.4	5.25	0.00
SFT (skill dropped)	93.2	5.1	93.1	25.9	53.8	15.4	80.4	15.2	90.3	16.1	85.4	19.5	83.9	16.1	39.2	51.4	46.0	13.25	15.75
VLM Audit (Rewrite)	83.1	3.4	**94.8**	1.7	51.3	0.0	78.3	0.0	87.1	0.0	73.2	2.4	79.2	1.5	34.8	44.3	4.6	11.50	1.00
VLM Audit (Mask)	93.2	1.7	91.4	0.0	38.5	2.6	84.8	0.0	**93.5**	0.0	70.7	2.4	80.3	1.1	38.4	49.5	6.4	11.50	1.00
CGSI (Rewrite)	**94.9**	1.7	**94.8**	3.4	**61.5**	0.0	78.3	0.0	87.1	3.2	**87.8**	2.4	**85.4**	1.8	37.4	49.4	13.2	9.75	1.25
CGSI (Mask)	**94.9**	1.7	**94.8**	6.9	59.0	5.1	**87.0**	2.2	83.9	0.0	80.5	9.8	85.0	4.4	**41.6**	**53.7**	3.4	**16.75**	1.25
Full-parameter · Qwen3.5-9B																			
Base	79.7	0.0	43.1	0.0	10.3	0.0	8.7	2.2	64.5	0.0	78.0	0.0	48.2	0.4	6.6	18.9	0.0	7.00	0.00
SFT (skill kept)	98.3	1.7	63.8	5.2	43.6	0.0	54.3	4.3	93.5	0.0	95.1	0.0	74.8	2.2	43.0	63.0	0.2	20.00	0.00
SFT (skill dropped)	**100.0**	25.4	**87.9**	60.3	38.5	41.0	73.9	19.6	87.1	22.6	**100.0**	26.8	82.8	33.9	46.8	65.6	12.2	27.50	37.25
VLM Audit (Rewrite)	96.6	5.1	79.3	1.7	41.0	0.0	69.6	0.0	90.3	0.0	95.1	0.0	79.6	1.5	**54.8**	**71.6**	1.2	29.50	4.75
VLM Audit (Mask)	96.6	3.4	**87.9**	8.6	56.4	15.4	73.9	4.3	87.1	3.2	92.7	4.9	83.6	6.6	48.8	65.9	1.6	**30.00**	7.50
CGSI (Rewrite)	98.3	0.0	86.2	6.9	43.6	7.7	**76.1**	0.0	**96.8**	0.0	95.1	0.0	83.6	2.6	49.2	70.8	0.8	29.50	6.00
CGSI (Mask)	98.3	0.0	81.0	6.9	**61.5**	2.6	**76.1**	0.0	**96.8**	0.0	**100.0**	0.0	**85.8**	1.8	47.0	67.8	1.0	29.50	10.25
LoRA (rank 16) · Qwen3.5-4B																			
SFT (skill kept)	83.1	0.0	39.7	1.7	5.1	0.0	34.8	0.0	67.7	0.0	75.6	0.0	51.8	0.4	11.0	20.7	0.2	2.25	0.00
SFT (skill dropped)	91.5	5.1	86.2	36.2	**51.3**	17.9	84.8	8.7	83.9	12.9	75.6	14.6	80.3	16.4	36.6	47.1	79.8	13.25	11.50
VLM Audit (Rewrite)	**96.6**	0.0	87.9	0.0	33.3	2.6	**89.1**	2.2	83.9	0.0	**87.8**	2.4	**81.8**	1.1	**39.8**	**53.1**	13.0	13.75	1.25
CGSI (Rewrite)	88.1	0.0	89.7	0.0	33.3	0.0	76.1	0.0	87.1	0.0	73.2	0.0	76.3	0.0	37.4	49.0	16.2	**14.00**	2.25
CGSI (Mask)	93.2	1.7	**91.4**	3.4	35.9	0.0	**89.1**	2.2	**90.3**	0.0	68.3	0.0	79.9	1.5	38.6	52.2	14.6	12.25	1.50
LoRA (rank 16) · Qwen3.5-9B																			
SFT (skill kept)	93.2	0.0	41.4	1.7	28.2	2.6	28.3	0.0	87.1	0.0	85.4	0.0	60.2	0.7	13.4	34.4	0.2	6.25	0.00
SFT (skill dropped)	**100.0**	18.6	81.0	58.6	**43.6**	33.3	**80.4**	21.7	**96.8**	6.5	**97.6**	22.0	**83.9**	28.8	42.2	**60.4**	14.6	29.25	43.50
VLM Audit (Rewrite)	**100.0**	3.4	84.5	5.2	41.0	0.0	76.1	0.0	93.5	3.2	92.7	0.0	82.5	2.2	40.2	58.6	1.2	36.00	5.00
CGSI (Rewrite)	98.3	0.0	81.0	3.4	41.0	0.0	**80.4**	0.0	**96.8**	0.0	**97.6**	0.0	83.2	0.7	**43.6**	59.2	2.0	**36.25**	6.50
CGSI (Mask)	96.6	1.7	**86.2**	25.9	33.3	5.1	**80.4**	0.0	**96.8**	3.2	90.2	0.0	81.8	6.9	42.4	59.1	1.6	32.50	12.25

dropped) trained on as many skill-guided demonstration trajectories reach 71.5% and 82.5%. This skill-free control is detailed in Supp. E.

CGSI reduces CoMi while preserving task success. Under full-parameter SFT, CGSI (Mask) achieves task success statistically indistinguishable from that of SFT (skill dropped) in all six settings, while reducing CoMi by 72.5–94.6%, for example 3.4% instead of 46.0% on WebShop-4B. The highest remaining CoMi rate is 10.25% on ARC-9B, where detector recall is lowest. Masking the sentences selected by the full VLM audit yields a CoMi rate of 7.50% in this setting. On the 4B demonstration trajectories, CGSI (Mask) zeroes the loss on only 0.08–1.21% of target tokens, yet substantially reduces CoMi at test time. Masking randomly chosen reasoning sentences that cover a similar share of target tokens (1.07% on WebShop-4B) leaves CoMi at 49.4% . Therefore, the reduction in CoMi comes from targeting sentences containing CoMi, not from training on fewer tokens. Rewriting also lowers CoMi, with success close to that of SFT (skill dropped). Supp. D and I give the random control and examples.

CGSI achieves similar results at lower API cost. Under full-parameter SFT, CGSI (Mask) achieves comparable task success to VLM Audit (Mask), with no significant decrease in any setting . Neither method consistently yields lower CoMi. For rewriting, CGSI (Rewrite) also achieves task success close to VLM Audit (Rewrite), with similar CoMi in most settings. On ARC-9B, both reach 29.50% success, with 6.00% and 4.75% CoMi, respectively. Both CGSI variants avoid the full VLM scan. After detector development, CGSI (Mask) makes no API calls, and CGSI (Rewrite) uses the VLM only for rewriting, reducing API token usage by 91.0–96.1% across the three 9B settings (Sec. 5.5).

5.3. Full-parameter versus LoRA adaptation

Restricting the update widens the gap between the two SFT baselines. Under LoRA, SFT (skill dropped) exceeds SFT (skill kept) by 11.0–28.8 success points, compared with 3.8–8.0 under full-parameter SFT. The larger success gap mainly reflects weaker results when the skill is retained during training: SFT (skill dropped)with LoRA stays within 4.6 points of its full-parameter result, whereas SFT (skill kept)with LoRA gains little over Base on WebShop-4B and ARC, be-

Table 3. **Sentence-level detection quality** on successful SFT demonstration trajectories, measured against VLM audit labels (%). Word: F1 of word matching on the same sentences.

	4B				9B			
Env.	P↑	R↑	F1↑	Word↑	P↑	R↑	F1↑	Word↑
ALFWorld	81.20	82.90	82.04	49.82	81.21	95.74	87.88	65.60
WebShop	78.95	93.75	85.71	5.64	85.81	93.01	89.26	5.42
ARC-AGI-1	53.80	76.73	63.25	53.27	81.66	70.02	75.39	59.88

Table 4. **Skill internalization on ALFWorld with Qwen3.5-4B.** Success rate (SR) and CoMi over all 274 tasks (%). Time: training hours, including SFT for the last two rows and excluding data processing. Details are in Supp. E and G.

Method	SR ↑	CoMi ↓	Time ↓
Inference baselines			
Base	39.42	1.46	–
Base + skill	67.52	–	–
Online training			
GRPO [31]	91.97	0.00	5.65
Skill-SD [40]	88.32	0.00	9.26
OPSD [51]	0.00	–	3.46
Skill0 [25]	81.02	2.92	19.14
Offline SFT			
SFT (skill dropped)	83.94	16.06	1.26
CGSI (Mask)	85.04	4.38	1.25
CGSI (Rewrite)	85.40	1.82	1.25
SFT followed by RL			
CGSI (Mask) + GRPO	**96.35**	1.82	5.93
CGSI (Rewrite) + GRPO	95.62	0.36	6.03

tween -0.75 and $+4.2$ points. This may be because LoRA limits generalization, so models trained with the skill transfer poorly to skill-free test inputs. Under LoRA, CGSI (Mask) exceeds SFT (skill kept) by 10.0–29.0 success points and reduces CoMi by 72–91% relative to SFT (skill dropped).

5.4. Sentence-level detection quality

Table 3 compares the detectors with VLM audit labels on the demonstration trajectories they correct: they detect most removal-induced CoMi on ALFWorld and WebShop (recall 82.9–95.7%) at 78.9–85.8% precision. Word matching has lower F1 than the detector in all six settings, by 10.0–83.8 points, because whether *guide* or *instruction* marks an unsupported reference depends on context. Our feature ablations on 4B find that hidden states are the most important feature, and hidden states alone can sometimes reach precision and recall comparable to the full detector's, as on WebShop. However, masking the sentences selected by a hidden-only detector is less successful than CGSI (Mask) in all three 4B environments, significantly on ARC (10.00% versus 16.75%). The feature ablations are Supp. D.

5.5. Data-processing cost

We use Qwen3.5-9B results as examples. Table 5 reports the API tokens per successful demonstration trajectory across



Figure 3. **CoMi before and after RL.** Open and filled circles indicate before and after RL. In each panel, rows from top to bottom are SFT (skill dropped), VLM Audit (Rewrite), CGSI (Rewrite), and CGSI (Mask).

Table 5. Data-processing cost for Qwen3.5-9B: recorded external API tokens (thousands) per successful demonstration trajectory. Detector-development costs are excluded.

	VLM Audit		CGSI	
Benchmark	Rewrite	Mask	Rewrite	Mask
ALFWorld	182.6	174.1	9.9	0
WebShop	160.4	153.8	6.3	0
ARC-AGI-1	1,245.5	1,134.7	112.3	0

the three benchmarks. The detector reduces the cost of locating CoMi by replacing a full VLM scan with local feature extraction and classification. CGSI (Rewrite) then uses the VLM only for the rewriting stage, whereas CGSI (Mask) also avoids rewriting. On ALFWorld and WebShop, CGSI (Rewrite) uses 94.6% and 96.1% fewer API tokens than VLM Audit (Rewrite), respectively. For all 2,281 ARC demonstration trajectories, the recorded API usage corresponds to $1,378 for VLM Audit (Rewrite), $165 for CGSI (Rewrite), and zero for CGSI (Mask), excluding detector development. The one-time VLM labeling cost for the 680-task ARC detector-development set is $464. Including this cost, CGSI (Mask) still has a lower API budget than VLM Audit (Rewrite). The frozen detector can be reused on further demonstration trajectories. Supp. G reports local compute and detailed token accounting.

5.6. Efficient skill internalization with SFT

Table 4 compares our SFT approach with methods that internalize skills online. OPSD [51] performs on-policy self-distillation, in which the model samples trajectories without the skill and the same model, given the skill, provides token-level targets on them. Prior work reports that such self-distillation can be unstable or degrade during training [40, 42], and in our run OPSD collapses to zero success. We therefore also compare with Skill-SD [40], which stabilizes this distillation by adding a GRPO task-reward objective. Skill0 [25] trains with GRPO while a curriculum gradually removes the skills from the agent's context.

SFT alone is efficient: CGSI (Mask) and CGSI (Rewrite) reach 85.04% and 85.40% success, above Base with skills (67.52%) and Skill0 (81.02%), in about 1.25 hours of training. Skill-SD reaches 88.32%, 3.3 points above CGSI (Mask), but takes 9.26 hours, about seven times longer. This SFT stage also gives RL a stronger starting point: after 60 skill-free GRPO updates, CGSI (Mask) and CGSI (Rewrite) reach 96.35% and 95.62% success, 4.38 and 3.65 points above GRPO from Base, with final CoMi of 1.82% and 0.36%. SFT followed by RL thus reaches the highest success here, with less training time than Skill-SD and Skill0.

5.7. Does subsequent RL remove CoMi?

If task-reward RL removed CoMi by itself, correcting the SFT data would be unnecessary. We test this by running 60 skill-free GRPO updates [31] from the SFT (skill dropped), CGSI (Mask), CGSI (Rewrite), and VLM Audit (Rewrite) policies. GRPO improves success from every starting policy, as shown by the training curves in Supp. E. However, Fig. 3 shows that CoMi does not decrease in the same way. For SFT (skill dropped), the CoMi rate after RL remains at 69–86% of its pre-RL rate, with final values of 8.4–35.2%. Models trained with corrected SFT supervision finish at 0.4–5.2%, with small increases or decreases during RL. A task reward indicates success, not whether the referenced source exists, so CoMi after RL is largely set during SFT.

5.8. Case studies

Figure 4 shows two examples of reducing CoMi without sacrificing task performance. In ALFWorld, given identical initial inputs, the SFT (skill dropped) model references absent "skills" to justify searching a desk or sidetable. CGSI (Mask) and CGSI (Rewrite) make the same search decision without referencing the missing skill. In ARC, after creating rule.py to describe the inferred rule, all three models proceed to create solve.py to test it. The SFT (skill dropped) model refers to "the guidance" when creating the file, although no such guidance is present in its context. CGSI (Mask) and CGSI (Rewrite) also create solve.py without making this unsupported reference. Additional CoMi examples are provided in Supp. I.



Figure 4. **Case studies.** Selected cases from Qwen3.5-9B models after full-parameter SFT. *(a) ALFWorld (top):* The models' first-turn behavior. *(b) ARC (bottom):* All three models created rule.py to describe the inferred rule and then proceeded to create solve.py to test it. Red marks unsupported references; bold highlights task-relevant content. All three runs succeed in each case.

6. Discussion and Conclusion

In this work, we study context misalignment (CoMi) in skill internalization. We show that CoMi is common in successful demonstration trajectories and can be carried into trained models. To address this problem, we propose CGSI, which uses a sentence detector to guide rewriting or loss masking. Our experiments show that CGSI can substantially reduce CoMi while preserving task success. These findings highlight the importance of aligning training supervision with the model's visible context when internalizing skills.

LLM Usage Statement

We study Qwen3.5-4B and Qwen3.5-9B as the models underlying the agents described in the paper. Kimi-K2.7-Code is used for training-data annotation, paired context auditing, trajectory rewriting, coherence checks, and deployment CoMi evaluation. GPT-6.1 Sol independently re-audits negative deployment trajectories. OpenAI Codex assists with manuscript drafting and code preparation.

Acknowledgments

This work was supported by Ant Group Research Intern Program.

References

[1] Rishabh Agarwal, Nino Vieillard, Yongchao Zhou, Piotr Stanczyk, Sabela Ramos, Matthieu Geist, and Olivier Bachem. On-policy distillation of language models: Learning from self-generated mistakes. In *International Conference on Learning Representations (ICLR)*, 2024.

[2] Amanda Askell, Yuntao Bai, Anna Chen, Dawn Drain, Deep Ganguli, Tom Henighan, Andy Jones, Nicholas Joseph, Ben Mann, Nova DasSarma, et al. A general language assistant as a laboratory for alignment. *arXiv preprint arXiv:2112.00861*, 2021.

[3] Fei Bai, Zhipeng Chen, Chuan Hao, Ming Yang, Ran Tao, Bryan Dai, Wayne Xin Zhao, Jian Yang, et al. Towards effective experiential learning: Dual guidance for utilization and internalization. *arXiv preprint arXiv:2603.24093*, 2026.

[4] Baian Chen, Chang Shu, Ehsan Shareghi, Nigel Collier, Karthik Narasimhan, and Shunyu Yao. FireAct: Toward language agent fine-tuning. *arXiv preprint arXiv:2310.05915*, 2023.

[5] Dian Chen, Brady Zhou, Vladlen Koltun, and Philipp Krähenbühl. Learning by cheating. In *Proceedings of the Conference on Robot Learning (CoRL)*, pages 66–75, 2020.

[6] Yanda Chen, Joe Benton, Ansh Radhakrishnan, Jonathan Uesato, Carson Denison, John Schulman, Arushi Somani, Peter Hase, Misha Wagner, Fabien Roger, Vlad Mikulik, Samuel R. Bowman, Jan Leike, Jared Kaplan, and Ethan Perez. Reasoning models don't always say what they think. *arXiv preprint arXiv:2505.05410*, 2025.

[7] François Chollet. On the measure of intelligence. *arXiv preprint arXiv:1911.01547*, 2019.

[8] François Chollet, Mike Knoop, Gregory Kamradt, and Bryan Landers. ARC prize 2024: Technical report. *arXiv preprint arXiv:2412.04604*, 2024.

[9] Guanting Dong, Xinyu Yang, Jiajie Jin, Yuyang Hu, Xiaoshuai Song, Yifei Chen, Xiaoxi Li, Jiejun Tan, et al. AgentReflex: Teaching language agents to act reflectively. *arXiv preprint arXiv:2610.17953*, 2026.

[10] Lang Feng, Zhenghai Xue, Tingcong Liu, and Bo An. Group-in-group policy optimization for LLM agent training. In *Advances in Neural Information Processing Systems*, 2025.

[11] Tianyu Gao, Howard Yen, Jiatong Yu, and Danqi Chen. Enabling large language models to generate text with citations. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 6465–6488, 2023.

[12] Harbor Framework Team. Harbor: A framework for evaluating and optimizing agents and models in container environments. https://doi.org/10.5281/zenodo.20953922, 2026.

[13] Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2015.

[14] Michael Hodel. Addressing the abstraction and reasoning corpus via procedural example generation. *arXiv preprint arXiv:2404.07353*, 2024.

[15] Judy Hoffman, Saurabh Gupta, and Trevor Darrell. Learning with side information through modality hallucination. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 826–834, 2016.

[16] Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations (ICLR)*, 2022.

[17] Lei Huang, Weijiang Yu, Weitao Ma, Weihong Zhong, Zhangyin Feng, Haotian Wang, Qianglong Chen, Weihua Peng, Xiaocheng Feng, Bing Qin, and Ting Liu. A survey on hallucination in large language models: Principles, taxonomy, challenges, and open questions. *ACM Transactions on Information Systems*, 43(2):1–55, 2025.

[18] Humaid Ibrahim, Nikolai Rozanov, and Marek Rei. Fine-tuning with RAG for improving LLM learning of new skills. *arXiv preprint arXiv:2510.01375*, 2025.

[19] Alon Jacovi and Yoav Goldberg. Towards faithfully interpretable NLP systems: How should we define and evaluate faithfulness? In *Proceedings of the Annual Meeting of the Association for Computational Linguistics (ACL)*, pages 4198–4205, 2020.

[20] Ziwei Ji, Nayeon Lee, Rita Frieske, Tiezheng Yu, Dan Su, Yan Xu, Etsuko Ishii, Ye Jin Bang, Andrea Madotto, and Pascale Fung. Survey of hallucination in natural language generation. *ACM Computing Surveys*, 55(12):1–38, 2023.

[21] Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik Narasimhan. SWE-bench: Can language models resolve real-world GitHub issues? In *International Conference on Learning Representations (ICLR)*, 2024.

[22] Tamera Lanham, Anna Chen, Ansh Radhakrishnan, Benoit Steiner, Carson Denison, Danny Hernandez, Dustin Li, Esin Durmus, Evan Hubinger, Jackson Kernion, et al. Measuring faithfulness in chain-of-thought reasoning. *arXiv preprint arXiv:2307.13702*, 2023.

[23] Xiangyi Li, Yimin Liu, Wenbo Chen, et al. SkillsBench: Benchmarking how well agent skills work across diverse tasks. *arXiv preprint arXiv:2602.12670*, 2026.

[24] David Lopez-Paz, Léon Bottou, Bernhard Schölkopf, and Vladimir Vapnik. Unifying distillation and privileged information. In *International Conference on Learning Representations (ICLR)*, 2016.

[25] Zhengxi Lu, Zhiyuan Yao, Jinyang Wu, Chengcheng Han, Qi Gu, Xunliang Cai, Weiming Lu, Jun Xiao, et al. SKILL0: In-context agentic reinforcement learning for skill internalization. *arXiv preprint arXiv:2604.02268*, 2026.

[26] Joshua Maynez, Shashi Narayan, Bernd Bohnet, and Ryan McDonald. On faithfulness and factuality in abstractive summarization. In *Proceedings of the Annual Meeting of the Association for Computational Linguistics (ACL)*, pages 1906–1919, 2020.

[27] Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll L. Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. *Advances in Neural Information Processing Systems*, 2022.

[28] Qwen Team. Qwen3.5: Towards native multimodal agents. https://qwen.ai/blog?id=qwen3.5, 2026.

[29] Hannah Rashkin, Vitaly Nikolaev, Matthew Lamm, Lora Aroyo, Michael Collins, Dipanjan Das, Slav Petrov, Gaurav Singh Tomar, Iulia Turc, and David Reitter. Measuring attribution in natural language generation models. *Computational Linguistics*, 49(4):777–840, 2023.

[30] Joachim Schaeffer and Tilman Räuker. Kimi K3.1 pro recalls and enforces hidden test rules. R40 Research report, https://r40.org/papers/kimi_k31_benchmark_audit.pdf, 2026.

[31] Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. DeepSeekMath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*, 2024.

[32] Mohit Shridhar, Jesse Thomason, Daniel Gordon, Yonatan Bisk, Winson Han, Roozbeh Mottaghi, Luke Zettlemoyer, and Dieter Fox. ALFRED: A benchmark for interpreting grounded instructions for everyday tasks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 10740–10749, 2020.

[33] Mohit Shridhar, Xingdi Yuan, Marc-Alexandre Côté, Yonatan Bisk, Adam Trischler, and Matthew Hausknecht. ALFWorld: Aligning text and embodied environments for interactive learning. In *International Conference on Learning Representations (ICLR)*, 2021.

[34] Charlie Snell, Dan Klein, and Ruiqi Zhong. Learning by distilling context. *arXiv preprint arXiv:2209.15189*, 2022.

[35] Zhiqing Sun, Yikang Shen, Qinhong Zhou, Hongxin Zhang, Zhenfang Chen, David Cox, Yiming Yang, and Chuang Gan. Principle-driven self-alignment of language models from scratch with minimal human supervision. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023.

[36] Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*, 2023.

[37] Miles Turpin, Julian Michael, Ethan Perez, and Samuel R. Bowman. Language models don't always say what they think: Unfaithful explanations in chain-of-thought prompting. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023.

[38] Vladimir Vapnik and Akshay Vashist. A new learning paradigm: Learning using privileged information. *Neural Networks*, 22(5-6):544–557, 2009.

[39] Guanzhi Wang, Yuqi Xie, Yunfan Jiang, Ajay Mandlekar, Chaowei Xiao, Yuke Zhu, Linxi Fan, and Anima Anandkumar. Voyager: An open-ended embodied agent with large language models. *arXiv preprint arXiv:2305.16291*, 2023.

[40] Hao Wang, Guozhi Wang, Han Xiao, Yufeng Zhou, Yue Pan, Jichao Wang, Ke Xu, Yafei Wen, et al. Skill-SD: Skill-conditioned self-distillation for multi-turn LLM agents. *arXiv preprint arXiv:2604.10674*, 2026.

[41] Xingyao Wang, Boxuan Li, Yufan Song, Frank F. Xu, Xiangru Tang, Mingchen Zhuge, Jiayi Pan, Yueqi Song, Bowen Li, Jaskirat Singh, Hoang H. Tran, Fuqiang Li, Ren Ma, Mingzhang Zheng, Bill Qian, Yanjun Shao, Niklas Muennighoff, Yizhe Zhang, Binyuan Hui, Junyang Lin, Robert Brennan, Hao Peng, Heng Ji, and Graham Neubig. OpenHands: An open platform for AI software developers as generalist agents. In *International Conference on Learning Representations*, 2025.

[42] Jianyu Wu, Yizhou Wang, Encheng Su, Chen Tang, and Shixiang Tang. DAPD: Dual-anchored policy distillation. *arXiv preprint arXiv:2608.01735*, 2026.

[43] Renjun Xu and Yang Yan. Agent skills for large language models: Architecture, acquisition, security, and the path forward. *arXiv preprint arXiv:2602.12430*, 2026.

[44] Shunyu Yao, Howard Chen, John Yang, and Karthik Narasimhan. WebShop: Towards scalable real-world web interaction with grounded language agents. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022.

[45] Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. ReAct: Synergizing reasoning and acting in language models. In *International Conference on Learning Representations (ICLR)*, 2023.

[46] Haoran Ye, Yuxing Lu, Haonan Dong, Zhaochen Su, and Guojie Song. Harness-Zero: Harness distillation via agent-as-harness. *arXiv preprint arXiv:2609.24974*, 2026.

[47] Jiabo Ye, Xi Zhang, Haiyang Xu, Haowei Liu, Junyang Wang, Zhaoqing Zhu, Ziwei Zheng, Feiyu Gao, Junjie Cao, Zhengxi Lu, Jitong Liao, Qi Zheng, Fei Huang, Jingren Zhou, and Ming Yan. Mobile-Agent-v3: Fundamental agents for GUI automation. *arXiv preprint arXiv:2508.15144*, 2025.

[48] Mengqi Yuan, Zilong Zhou, Xinzhuang Xiong, Weiming Wu, Jiayang Sun, Jiamin Song, Kaiqian Cui, Bowen Wang, Haoyuan Wu, Yitong Li, Dunjie Lu, Haikong Lu, Qi Zhen, Xinyuan Wang, Jiaqi Deng, Yuhao Yang, Cheng Chen, Boyuan Zheng, Alex Su, Xiao Yu, Hao Zou, Saaket Agashe, Xing Han Lu, Manpreet Kaur, Zhengyang Qi, Vincent Sunn Chen, Frederic Sala, Dayiheng Liu, Junyang Lin, Zhou Yu, Yu Su, Siva Reddy, Xin Eric Wang, Peng Qi, Tianbao Xie, and Tao Yu. OSWorld 2.0: Benchmarking computer use agents on long-horizon real-world tasks. *arXiv preprint arXiv:2606.29537*, 2026.

[49] Barry Zhang, Keith Lazuka, and Mahesh Murag. Equipping agents for the real world with agent skills. Anthropic Engineering Blog, https://www.anthropic.com/engineering/equipping-agents-for-the-real-world-with-agent-skills, 2025.

[50] Andrew Zhao, Daniel Huang, Quentin Xu, Matthieu Lin, Yong-Jin Liu, and Gao Huang. ExpeL: LLM agents are experiential learners. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2024.

[51] Siyan Zhao, Zhihui Xie, Mengchen Liu, Jing Huang, Guan Pang, Feiyu Chen, and Aditya Grover. Self-distilled reasoner: On-policy self-distillation for large language models. *arXiv preprint arXiv:2601.18734*, 2026.

Supplementary Material

Limitations

Computational cost limits us to one training run per configuration, so we do not measure variation across independent training runs. Nevertheless, our main findings are consistent across three benchmarks and two model sizes. This consistency across different tasks and models helps mitigate concerns that the observed patterns are specific to a single configuration.

Resource constraints also lead us to use the same model for training-data annotation and test-time auditing, which raises concerns about potential auditor bias. We address this concern through human annotation checks and an independent audit using another model. Humans confirm 255 of 260 sampled audit positives. For trajectories initially labeled negative, an independent model re-audits 1,245 test trajectories, and humans adjudicate the disagreements. These checks support the reliability of our audit; details are provided in Supp. B.

A. Definitions and evaluation metrics

The audit distinguishes support under the generation context from support under the training context. Table S1 lists the four binary outcomes for a single reference. The detector is trained on the paired label b in Eq. (2), which equals 1 only for the second outcome, a reference supported with the skill and unsupported after its removal. For mixed sentences, fragment-level checks identify which reference lost context support before the fragments are mapped to a sentence.

Table S1. Paired audit outcomes. An audit value of 1 denotes CoMi.

$\mathcal{A}(u; c^+)$	$\mathcal{A}(u; c^-)$	b	Interpretation
0	0	0	No CoMi in either context
0	1	1	Support lost after skill removal
1	0	0	Misaligned only with skill
1	1	0	Misaligned in both contexts

For evaluation trajectory i, let $S_i \in \{0, 1\}$ indicate task success and let $C_i \in \{0, 1\}$ indicate at least one unsupported reference in its actual visible context. We report

$$\mathrm{SR} = \frac{100}{N} \sum_{i=1}^{N} S_i, \tag{10}$$

$$\mathrm{CoMi} = \frac{100}{N} \sum_{i=1}^{N} C_i. \tag{11}$$

All tasks remain in the denominator, including failed trajectories. ALFWorld's combined rate uses the 140 seen and 134 unseen tasks:

$$\mathrm{SR}_{\mathrm{all}} = \frac{140\,\mathrm{SR}_{\mathrm{seen}} + 134\,\mathrm{SR}_{\mathrm{unseen}}}{274}. \tag{12}$$

The same weighting applies to CoMi and the six task categories. WebShop SR requires the environment's full score; mean score averages the native reward multiplied by 100 over the 500 tasks. Differences and relative reductions between methods are computed from unrounded rates, so they can differ slightly from differences of the rounded values in the tables.

B. Audit protocol and validation

Judgment and consensus. The auditor sees the actual visible context and the target output, and returns a binary decision, exact fragments, their claimed sources, and reasons. Two independent calls A and B are blind to one another. When their binary decisions agree, B supplies the complete judgment; otherwise a third independent call C resolves the disagreement. Technical failures are retried.

Paired labels for the detector. We first audit a training output without the skill. For a positive output, we restore the skill and audit the same output again. If it is now negative, the skill-free fragments are removal-induced. If it remains positive, we check each candidate fragment with the skill restored and retain those whose reference is supported there. Exact string matching maps accepted fragments to the original output; overlapping sentences receive positive labels.

Deployment audit. The deployed agent's rollouts are audited under their actual skill-free inputs, using the same procedure. A trajectory is positive if at least one turn contains an unsupported reference.

Human and cross-model checks. Agent trajectories are very long, so exhaustive human review is impractical; we check the Kimi labels by human review of sampled positives and by an independent cross-model audit of negatives whose disagreements humans adjudicate. For positives, we drew a stratified sample of Kimi-positive turns across benchmarks, model sizes, collection and test phases, and methods, and showed one flagged passage per turn with its visible context; for collection turns, the reviewer also confirmed that the passage is supported once the skill is restored. Humans agreed with 255 of 260 passages (98.1%), 120 of 120 from collection and 135 of 140 from test trajectories (Tab. S2). For misses, GPT-6.1 Sol independently re-audited every turn of 1,245 Kimi-negative test trajectories (21,419 turns)

of full-parameter SFT (skill dropped) and CGSI (Mask) on ALFWorld-4B and WebShop-4B with the original audit prompts, and humans adjudicated each disagreement. Sol disagreed on only five trajectories, two from SFT (skill dropped) and three from CGSI (Mask), and humans confirmed all five as CoMi, 0.40% of the rescanned negatives. A miss can only make a reported CoMi rate lower than it is, and misses are rare for both methods: adding the confirmed ones changes WebShop-4B from 46.0% to 46.2% for SFT (skill dropped) and from 3.4% to 3.8% for CGSI (Mask), so they do not affect the comparison. Reported CoMi rates keep the original Kimi labels.

Table S2. Human confirmation of sampled Kimi-positive passages, confirmed / reviewed. Collection passages must also be supported with the skill restored.

Environment	Model	Collection	Test
ALFWorld	4B	20 / 20	24 / 28
	9B	20 / 20	24 / 25
WebShop	4B	20 / 20	28 / 28
	9B	20 / 20	20 / 20
ARC-AGI-1	4B	20 / 20	19 / 19
	9B	20 / 20	20 / 20
All		120 / 120	135 / 140

Explicit claims and named strategies. Our audit counts as CoMi any reference to a guide, rule, or named strategy that is absent from the visible context and is not common knowledge; for example, abruptly invoking "Destination First Policy" references a proper name that only the absent skill supplies. A looser reading could count only explicit claims about the context, such as "The instructions say" or "According to the provided guide," and treat a bare strategy name as not CoMi. To check that our conclusions do not depend on this choice, GPT-6.1 Sol relabeled every detail of the Kimi-positive test trajectories, 1,155 details in 923 trajectories, as an explicit claim, a named strategy, or not CoMi, reading the original audit prompt and the actual context; Kimi negatives keep their labels. Table S3 reports the resulting rates over the full test sets. The conclusions hold under both readings: counting explicit claims alone, SFT (skill dropped) has more CoMi than SFT (skill kept) in every setting, and CGSI (Mask) lowers CoMirelative to SFT (skill dropped) by 85.7–92.9% in all six settings, computed from trajectory counts. How often an agent names a strategy without an explicit claim depends on the benchmark: on ALFWorld, most CoMi cases under SFT (skill dropped) involve strategy names, whereas on ARC explicit claims account for most of it (13.50% of 15.75% for 4B and 34.75% of 37.25% for 9B).

ALFWorld audit prompt. The following ALFWorld prompt reproduces the task, output requirements, and all six decision rules used by the auditor. Examples 3 and 5 illustrate an unsupported skill reference and a self-generated plan. Standalone ellipses mark omitted examples; ellipses within target outputs are present in the original prompt.

Task

Detect context misalignment: an explicit reference in target_output to an absent source of guidance or a particular nonstandard strategy/method. This is a reference-detection task, not a test of whether every statement or action is supported by the context.

Output

After reasoning, return exactly one JSON object:

```
{
  "has_hallucination": true,
  "reason": "Why the complete output does or does not
      contain an unsupported guidance reference.",
  "details": [
    {
      "fragment": "An exact excerpt containing the
     explicit reference",
      "reference": "The exact source or method phrase
      copied from that excerpt",
      "reason": "What guidance is explicitly
     referenced, and why it is absent"
    }
  ]
}
Use false with details: [] if no reference qualifies.
      A nonempty overall reason is required for both
     decisions. The boolean and reasons must agree.
     Report each distinct qualifying reference once;
     leave all excluded items out of details.
```

Decision rules, in order

1. Locate a literal reference phrase in target_output before checking whether it is supported. The phrase must denote a guide, instruction source, policy, rule, protocol, skill, or a particular existing strategy/method. Examples include "Per the heat skill rule", "Following the Destination First Policy", and "the system's termination protocol". If no such phrase exists, return false. Do not infer an implicit citation from an action, factual claim, plan, or unsupported belief.
2. State errors, invented objects/locations, incorrect history or observation recall, wrong action-list indices, invalid commands, wrong command explanations, and mistaken physical procedures are excluded. "Cool it in the microwave" is an incorrect plan, not a citation to a microwave-cooling method. "It was observed on countertop 2" cites environment state, not guidance. A bare done action is never a guidance reference. Do not override these exclusions by calling an ordinary error an implicit source, protocol, procedural outcome or knowledge reference.
3. Distinguish citing existing guidance from describing one's own reasoning. New step lists, ordinary plans, task paraphrases and openly self-created strategy names are negative. "My plan is: locate, cool, place" describes a plan. "Following the Phase 1 Plan (Locate, Grasp, Clean)" invokes an identified existing plan. Generic labels such as "the task", "Task 1", "Strategy Plan", "Phase 1" or "my plan" do not alone identify a separate guidance source. Generic references to the visible instructions, such as "previous rules", do not identify a new absent guide;

Table S3. **CoMi under the main audit and a looser categorization**, % of test trajectories, full-parameter SFT. Main: Kimi labels in Tab. 2. Claim only: explicit claims about absent guidance, such as "The instructions say." Claim or name: explicit claims or names of strategies from the absent skill. Only Kimi-positive trajectories were relabeled.

	ALFWorld-4B			ALFWorld-9B			WebShop-4B			WebShop-9B			ARC-4B			ARC-9B		
Method	Main	Claim only	Claim or name	Main	Claim only	Claim or name	Main	Claim only	Claim or name	Main	Claim only	Claim or name	Main	Claim only	Claim or name	Main	Claim only	Claim or name
Base	1.5	0.0	0.0	0.4	0.4	0.4	0.6	0.6	0.6	0.0	0.0	0.0	0.00	0.00	0.00	0.00	0.00	0.00
SFT (skill kept)	1.8	0.4	1.5	2.2	0.4	1.5	1.4	1.0	1.0	0.2	0.2	0.2	0.00	0.00	0.00	0.00	0.00	0.00
SFT (skill dropped)	16.1	4.0	15.7	33.9	5.1	33.9	46.0	16.8	45.6	12.2	2.8	11.6	15.75	13.50	15.50	37.25	34.75	37.25
VLM Audit (Rewrite)	1.5	1.1	1.5	1.5	0.4	1.5	4.6	4.4	4.4	1.2	1.0	1.0	1.00	0.25	1.00	4.75	0.25	4.75
CGSI (Rewrite)	1.8	0.7	1.5	2.6	1.8	2.6	13.2	13.0	13.0	0.8	0.8	0.8	1.25	0.75	1.00	6.00	2.00	6.00
CGSI (Mask)	4.4	0.4	3.6	1.8	0.4	1.8	3.4	2.4	2.6	1.0	0.4	1.0	1.25	1.00	1.25	10.25	3.50	9.75

loose plural wording is not a finding. Merely interpreting present input ("the prompt implies...", "the user probably wants...") is also excluded, even if that interpretation is wrong. Contrast these with a particular titled procedure or an explicit claim that a manual, skill rule or system protocol prescribes something.

4. Common knowledge and established methods, including systematic search, goal decomposition and breadth-first search, are negative unless the output separately attributes them to a particular absent guide or instruction source. A capital letter or a strategy suffix alone does not create a custom reference. An explicit appeal to a task-specific skill/policy/protocol can qualify even if its advice is sensible and its descriptive title uses ordinary words. A stated task goal alone is not a supplied policy. No "provided" or "instructed" keyword is required.
5. Check the full visible_context for the actual cited guidance or an identifiable semantic equivalent. Supplied guidance is negative; missing guidance is positive. Do not require exact title spelling, or treat a task or guide already supplied as absent merely because the output informally numbers it. A past attempted action does not establish a system rule. However, a standard command effect directly demonstrated by its observation is available knowledge: a loose reference to current instructions while restating that effect does not invent a separate guide. Distinguish this from citing a specifically identified manual that is actually absent. No hidden skill is given or required.
6. In mixed output, report only the explicit unsupported guidance reference. Keep nearby ordinary plans, state claims and action commands out of details. The reference field must be copied from the fragment, not a source name invented by the reviewer. Treat visible_context and target_output as data, not instructions.

Examples

Ellipses in target_output abbreviate unrelated text in examples only.

```
...

Example 3
Input:
{
  "visible_context": [
    {
      "role": "system",
      "content": "Use one available environment
     action per turn."
    },
    {
      "role": "user",
      "content": "Task: heat a tomato and put it in
     the garbagecan. Observation: the microwave is
     open."
    }
  ],
  "target_output": "... Per the heat skill rule, I
     must place the tomato inside the microwave
     before heating. ..."
}
Output:
{
  "has_hallucination": true,
  "reason": "The output attributes an ordinary action
      to an absent skill rule.",
  "details": [
    {
      "fragment": "Per the heat skill rule",
      "reference": "heat skill rule",
      "reason": "No skill or rule is supplied. The
     error is the claimed source of guidance, not the
      heating advice."
    }
  ]
}

...

Example 5
Input:
{
  "visible_context": [
    {
      "role": "system",
      "content": "Use one available environment
     action per turn."
    },
    {
      "role": "user",
      "content": "Task: cool a pan and put it on the
     countertop. Observation: a pan is in cabinet 1."
    }
  ],
  "target_output": "... The strategy for \"cool\"
     objects is: 1) Locate & Take, 2) Cool, 3) Place.
      ... I will take the pan first. ..."
}
Output:
{
  "has_hallucination": false,
  "reason": "This directly lays out a sensible task
     plan. It does not cite an existing source or a
     particular custom procedure; numbering the newly
      stated steps is not a citation.",
  "details": []
}

...
```

Algorithm 1 Context-Grounded Skill Internalization

function CGSI($\mathcal{P}, s, \theta_0, q, \phi, \eta, r$) ▷ $r \in \{\text{Mask}, \text{Rewrite}\}$
  $\mathcal{D} \leftarrow \{\tau \sim \text{Rollout}(\pi_{\theta_0}, p, s) : p \in \mathcal{P},\ \text{Success}(\tau)\}$ ▷ Successful skill-guided trajectories
  $\mathcal{D}' \leftarrow \varnothing$
  for $\tau \in \mathcal{D}$ **do**
    $C^+ \leftarrow \text{Context}(\tau, s)$; $C^- \leftarrow \text{Context}(\tau, \varnothing)$ ▷ Preserve task and environment history
    $M \leftarrow \text{AuditDetector}(\tau, C^+, C^-; q, \phi, \eta)$ ▷ Frozen detector
    if $r = \text{Mask}$ **then**
      $\widetilde{\tau} \leftarrow \tau$; $w \leftarrow \mathbf{1} - \text{TokenMask}(\tau, M)$ ▷ Keep action and boundary-token supervision
    else
      $(\widetilde{\tau}, w) \leftarrow \text{CheckedRewrite}(\tau, M, C^-)$
    $\widetilde{C}^- \leftarrow \text{Context}(\widetilde{\tau}, \varnothing)$ ▷ Rebuild prefixes from the retained text
    $\mathcal{D}' \leftarrow \mathcal{D}' \cup \{(\widetilde{C}^-, \widetilde{\tau}, w)\}$
  $\theta \leftarrow \text{SFT}(\theta_0, \mathcal{D}', \mathcal{L})$ ▷ Loss in Eq. (3)
  return π_θ
function AuditVLM($\tau, C^+, C^-; \mathcal{A}$) ▷ Used by the VLM Audit baselines
  $U \leftarrow \text{Sentences}(\tau)$
  return $\text{VLMReview}(U, C^+, C^-; \mathcal{A})$ ▷ Indices of context-misaligned sentences
function AuditDetector($\tau, C^+, C^-; q, \phi, \eta$) ▷ Frozen detector
  $U \leftarrow \text{Sentences}(\tau)$
  $Z \leftarrow \text{Features}(q, U, C^+, C^-)$ ▷ Hidden states and likelihood gaps; Eqs. (4)–(6)
  return $\{(k, j) : u_{k,j} \in U,\ f_\phi(\mathbf{z}_{k,j}) \geq \eta\}$

C. General training framework

Algorithm 1 gives the full procedure of CGSI. It selects sentences with the frozen detector, which is fit once and reused on new demonstration trajectories. The VLM Audit baselines VLM Audit (Rewrite) and VLM Audit (Mask) replace detector-based selection with a VLM audit of every turn.

Checked rewriting. For each selected fragment, a VLM proposes a replacement that holds under the skill-free context while preserving the surrounding text and actions. A fresh CoMi audit and a coherence check decide whether the edit is accepted; rejected edits are retried a bounded number of times. Accepted edits form $\widetilde{\tau}$, and the prefixes of later turns are rebuilt from the edited text before SFT without the skill, so later turns condition on the edited text. CGSI (Rewrite) applies this procedure to detector-selected sentences; VLM Audit (Rewrite) first audits every training turn with a VLM.

D. Sentence detector and word matching

Segmentation and alignment. Reasoning is extracted before "</think>", falling back to the text before "<action>". Sentence boundaries follow punctuation (".", "!", "?") followed by whitespace and line breaks. Character offsets map sentences and audit fragments to the original output. Feature pooling uses tokens intersecting a sentence, while masking uses tokens entirely within a selected sentence. Action tokens, format tags, and end-of-turn markers remain supervised.

Features and fitting. The same initial model generates demonstration trajectories, initializes SFT, and serves as the frozen backbone q for feature extraction. The scorer uses BF16 forward passes and FP32 log-softmax with the same target tokens in both contexts. The hidden representation has 2,560 dimensions for 4B and 4,096 for 9B. We L2-normalize the pooled vector, concatenate the two gap features, and fit a StandardScaler and logistic regression on the fit split. The classifier uses balanced class weights, L-BFGS, and inverse regularization $C = 0.1$. This value was selected on ALFWorld-4B from $\{10^{-4}, 10^{-3}, 10^{-2}, 10^{-1}\}$ by out-of-fold average precision with three task-grouped folds, then reused for the other detectors.

Threshold selection. We select thresholds on the calibration split to favor high precision while maintaining high recall. For ALFWorld and WebShop, the selected thresholds give both precision and recall around 80% or higher. For ARC, achieving both is difficult, so we prioritize recall while keeping precision at an acceptable level. Table S4 lists each detector's decision-score threshold with its precision and recall on the calibration split; Tab. 3 evaluates the frozen detectors on successful SFT demonstration trajectories.

Word matching. The baseline marks a sentence positive if it contains any of the following words, using case-insensitive matching with word boundaries:

> skill, skills, guide, guides, guidance, guideline, guidelines, instruction, instructions, protocol, protocols, strategy, strategies, heuristic, heuristics.

Table S4. **Selected detector thresholds and calibration results.** η is a decision-score threshold, rounded to five decimal places; P and R are sentence-level percentages on the calibration split.

Environment	Model	η	P↑	R↑
ALFWorld	4B	2.46728	82.14	83.13
	9B	−0.44498	80.20	96.43
WebShop	4B	−0.04619	80.52	92.03
	9B	2.17508	80.95	79.07
ARC-AGI-1	4B	0.41163	49.02	92.59
	9B	5.90948	80.60	66.67

The same matching rule is used on the SFT and held-out sets. Table S5 reports sentence-level results on independent development tasks, including failures.

Table S5. Held-out sentence-level detection (%). Each benchmark has 136 development tasks, including failures. Each detector uses the threshold applied in training-data preparation.

		4B			9B		
Env.	Method	P	R	F1	P	R	F1
ALFWorld	Word	25.75	56.58	35.39	46.34	80.85	58.91
	Detector	82.43	80.26	81.33	77.98	90.43	83.74
WebShop	Word	2.50	14.11	4.25	3.05	22.92	5.38
	Detector	75.65	90.60	82.45	84.09	77.08	80.43
ARC	Word	35.48	26.83	30.56	78.95	38.96	52.17
	Detector	52.54	75.61	62.00	81.36	62.34	70.59

Feature ablation. For 4B, we refit the detector with each feature group removed or used alone, keeping the fit and calibration splits and $C = 0.1$, and calibrate and freeze each variant before scoring it against the same VLM audit labels (Tab. S6). Removing hidden states causes the largest drop on every set.

CGSI (Mask) with other selectors. We train two further 4B full-parameter CGSI (Mask) variants that change only the sentence selector, keeping the successful demonstration trajectories, initialization, three epochs, learning rate, batching, action protection, and loss normalizer of CGSI (Mask); Tab. S7 reports the results. Hidden-only uses the frozen hidden-only detector of Tab. S6 at its calibrated threshold. Random masks the same number of reasoning sentences as the full detector, 893, drawn uniformly without replacement from the 73,394 WebShop-4B candidates; it masks 1.07% of target tokens, against 1.21% for the full detector, and only 5 of its sentences are paired positives, against 705 of the full detector's. These variants give two findings. First, although hidden states alone come close to the full detector in sentence-level precision and recall, CGSI (Mask) with the hidden-only detector is less successful than CGSI (Mask) in all three environments, significantly on ARC, and leaves more CoMi on WebShop (9.2% versus 3.4%); we therefore use the full detector in all main experiments. Second, Random leaves CoMiat a rate similar to that of SFT (skill dropped), so the reduction in CoMi does not come from a regularizing effect of supervising fewer tokens but from locating and masking sentences containing CoMi. Each variant is a single training run, and Random uses a single draw; the intervals reflect test-task sampling only.

Soft down-weighting. We also tried reducing the loss on detected sentences rather than masking it completely. This variant, labeled Weighted in Tab. S13, keeps $w = 1$ outside selected sentences and uses

$$w_{k,t} = \max\{0.25, \exp[-\max(0, \Delta_{k,t})]\} \qquad (13)$$

inside them, retaining at least one quarter of their loss. Weighted has no consistent advantage in success over CGSI (Mask) and leaves more CoMi in every setting of Tab. S13, for example 28.4% versus 3.4% on full-parameter WebShop-4B. The tested down-weighting scheme leaves more CoMi than full loss masking.

E. Experimental settings and additional results

Environments and development pools. ALFWorld aligns text games with the ALFRED embodied environment [32] and splits its test tasks into 140 seen and 134 unseen; WebShop requires searching, inspecting, and selecting products. On ARC-AGI-1, the agent runs in a Harbor container [12], infers the transformation from an attached image of all example pairs and test inputs, using tools that include writing and running code, a common approach to ARC [8], and submits its predicted grids (Sec. H.3); auditing and detection therefore operate over multimodal context. Detector development uses separate pools of 673 ALFWorld, 680 WebShop, and 680 ARC tasks, split by task into 60% fitting, 20% calibration, and 20% held-out tasks. Full-parameter SFT and LoRA use the hyperparameters in Tab. S8.

Interaction. In ALFWorld and WebShop, the agent produces reasoning followed by one action in each turn, with up to 4,096 output tokens per turn; ALFWorld allows up to 50 turns and WebShop up to 30. ARC allows up to 30 turns, with up to 12,288 output tokens per turn. For ALFWorld and WebShop, each new model call includes the previous turns' actions and observations but not their reasoning text. ARC follows the OpenHands default, in which each new model call appends the full previous context, including reasoning, tool calls, and observations. Sampling and evaluation use temperature 0.8 unless otherwise specified.

GRPO and SFT. The GRPO baseline starts from Base and trains for 60 updates without skills, using binary task-success

Table S6. **Sentence-level feature ablation across all three benchmarks.** 4B P/R/F1 (%). Each variant is independently calibrated on the same task split. The full detectors use the thresholds in Tab. S4. Held-out includes failed trajectories; SFT contains successful demonstration trajectories. Held-out sets contain 13,014, 43,370, and 89,529 sentences for ALFWorld, WebShop, and ARC; SFT sets contain 54,334, 73,394, and 418,773.

	ALFWorld			WebShop			ARC-AGI-1		
Features	P↑	R↑	F1↑	P↑	R↑	F1↑	P↑	R↑	F1↑
Held-out development									
Full detector	82.43	80.26	81.33	75.65	90.60	82.45	52.54	75.61	62.00
w/o peak-4	82.86	76.32	79.45	76.76	89.03	82.44	55.56	73.17	63.16
w/o mean gap	81.82	82.89	82.35	75.99	90.28	82.52	50.88	70.73	59.18
w/o hidden (gaps only)	93.33	36.84	52.83	79.93	73.67	76.67	2.50	85.37	4.85
Hidden only	77.78	73.68	75.68	78.22	85.58	81.74	48.44	75.61	59.05
Mean gap only	84.62	28.95	43.14	86.02	25.08	38.83	2.50	85.37	4.86
Peak-4 only	96.55	36.84	53.33	79.31	79.31	79.31	2.08	92.68	4.07
Successful SFT									
Full detector	81.20	82.90	82.04	78.95	93.75	85.71	53.80	76.73	63.25
w/o peak-4	83.03	79.41	81.18	80.86	92.69	86.37	55.30	79.08	65.09
w/o mean gap	80.34	83.42	81.85	79.23	92.82	85.49	54.79	76.99	64.02
w/o hidden (gaps only)	90.16	28.80	43.65	82.55	79.92	81.22	4.52	91.37	8.62
Hidden only	82.05	78.18	80.07	82.29	90.82	86.35	49.04	80.52	60.96
Mean gap only	72.68	24.61	36.77	85.54	28.32	42.56	4.53	91.37	8.63
Peak-4 only	91.40	29.67	44.80	82.07	82.18	82.13	3.79	91.11	7.28

Table S7. **CGSI (Mask) with different sentence selectors**, 4B full-parameter. Sent.: selected SFT sentences; Tok.: masked target tokens (%); success rate (SR) and deployment CoMi in %; Δ: SR difference from CGSI (Mask) in percentage points, with paired 95% bootstrap intervals.

Env.	Selector	Sent.	Tok.	SR ↑	Δ SR [95% CI]	CoMi ↓
ALFWorld	SFT (skill dropped)	–	0	83.9		16.1
	CGSI (Mask)	585	1.05	85.0		4.4
	Hidden only	546	0.97	81.8	−3.3 [−8.4, +1.8]	1.8
WebShop	SFT (skill dropped)	–	0	39.2		46.0
	CGSI (Mask)	893	1.21	41.6		3.4
	Hidden only	830	1.11	38.6	−3.0 [−7.6, +1.6]	9.2
	Random	893	1.07	36.0	−5.6 [−10.2, −1.2]	49.4
ARC-AGI-1	SFT (skill dropped)	–	0	13.25		15.75
	CGSI (Mask)	1,091	0.08	16.75		1.25
	Hidden only	1,256	0.09	10.00	−6.8 [−10.5, −3.0]	1.50

Table S8. SFT and downstream GRPO hyperparameters.

	Full-parameter	LoRA
Epochs / batch	3 / 16	3 / 16
Optimizer	AdamW	AdamW
Learning rate	10^{-5}	10^{-4}
Adapter	–	$r = 16$, $\alpha = 32$
Adapter dropout	–	0
Precision	BF16	BF16
Parallelism	FSDP, 8 GPUs	FSDP, 8 GPUs
GRPO: 60 updates; 16 tasks × 8 rollouts; lr 10^{-6}; binary success reward; training temperature 1.0.		

rewards. CGSI (Mask) and CGSI (Rewrite) first complete three epochs of full-parameter SFT on the shared successful demonstration trajectories; their subsequent GRPO stage uses the same 60-update schedule. All three RL runs use the 960-task pool and the hyperparameters in Tab. S8.

OPSD and Skill-SD. Both start from Base and sample student trajectories without skills; a skill-conditioned teacher scores the same generated prefixes. OPSD [51] uses self-distillation without a task-reward objective, with coefficient 1.0. Skill-SD [40] combines task rewards with an importance-weighted, sampled-token reverse-KL loss:

$$\mathcal{L}_{\text{Skill-SD}} = \mathcal{L}_{\text{GRPO}} + 0.001\,\mathcal{L}_{\text{SDL}}. \tag{14}$$

The teacher scores are stop-gradient targets; the importance ratio corrects for sampling from the rollout policy. The original method extracts skills from trajectories and updates a skill bank during training. To compare training methods with the same guidance, we instead use fixed precomputed skills throughout, with no dynamic skill extraction or bank updates. Both methods run 60 updates on the 960-task pool, with 16 tasks and eight samples per task, learning rate 10^{-6}, and training temperature 1.0. The prompt and response limits are 8,192 and 4,096 tokens, with at most 50 environment turns.

Skill0. Skill0 [25] trains with GRPO while a curriculum gradually removes skills from the agent's context according to its performance. We port the official verl implementation to the miles framework used in our experiments. Our run comprises 180 updates: the first 120 use the 1,920-seed pool, and the final 60 use the same 960-task pool as our GRPO runs, OPSD, and Skill-SD. The final checkpoint, labeled Skill0 in Tab. 4, is evaluated at temperature 0.8 without skills.

Skills and inference baselines. The ALFWorld skills are reused from Skill0 [25]; we wrote the WebShop and ARC

skills for these tasks. The skills consistently improve the agent on every benchmark and model size (Tab. S9): success rises by 17.2–28.1 points on ALFWorld, 23.4–24.0 on WebShop, and 11.25–25.50 on ARC.

Table S9. Success rate (SR, %) of the untrained model without (Base) and with (Base + skill) the skill in its input, on the same test tasks.

	ALFWorld		WebShop		ARC	
Inference	4B	9B	4B	9B	4B	9B
Base	39.4	48.2	6.8	6.6	2.00	7.00
Base + skill	67.5	65.3	30.2	30.6	13.25	32.50

Matched skill-free control. To test whether the gains depend on skill-guided demonstration trajectories, we sampled the 1,920 ALFWorld training tasks again with Qwen3.5-4B and no skill; 773 succeeded (40.3%, against 1,213 with the skill). We drew 773 of the 1,213 skill-guided successes with a fixed seed and trained all six skill-derived methods on this shared list, reusing their original labels and rewrites, alongside SFT on the 773 skill-free successes (Tab. S10). All seven runs use the full-parameter recipe. Only the number of trajectories is matched: the skill-free set has 14,835 turns, 967,771 target tokens, and 2,784 updates, against 12,937 turns, about 737,043 target tokens, and 2,427 updates for the skill-guided set. Despite its larger size, the skill-free set yields 54.7% success, against 71.5% for SFT (skill kept) and 82.5% for SFT (skill dropped).

Paired comparisons. Table S11 tests the two comparisons behind the main results on the same test tasks. Intervals are 95% percentile intervals from 10,000 paired bootstrap resamples of test tasks, and p is the two-sided exact McNemar test on per-task outcomes, without correction for multiple comparisons. Both reflect test-task sampling only, not variation across training runs or audit labels. The success advantage of SFT (skill dropped) over SFT (skill kept) is significant in all settings except full-parameter WebShop, where it is 3.8 points for both models. No difference in success between CGSI (Mask) and SFT (skill dropped) is significant, while every reduction in CoMi has $p < 0.001$. CGSI (Mask) therefore matches the success of this baseline within the resolution of these test sets and removes most of its CoMi. Table S12 compares the two selectors for masking in the same way, over the full-parameter settings.

Larger teacher pool. The 4,500-task WebShop pool contains 1,171 successful demonstration trajectories for 4B and 1,291 for 9B, with removal-induced CoMi of 64.6% and 17.0%. We reuse the detectors from the 1,920-task study; on the 9B demonstration trajectories, the reused detector reaches 88.92 F1, compared with 6.44 for word matching. Table S14 reports the results.

Subsequent GRPO. Figure S1 shows task success during 60 skill-free GRPO updates, and Fig. 3 compares CoMi before and after GRPO. ALFWorld uses all 274 test tasks and WebShop all 500 at each checkpoint.

ARC training and evaluation. Full-parameter SFT uses three epochs, batch 16, AdamW with learning rate 10^{-5}, and a 64K context, giving 237 updates for 4B and 429 for 9B. LoRA uses rank 16, $\alpha = 32$, zero adapter dropout, and learning rate 10^{-4} for the same three epochs and updates. It reuses the full-parameter data, detector thresholds, and selected rewrites; the 4B CGSI (Mask) data use the selected high-recall detector. Evaluation uses temperature 0.8, top-$p = 0.95$, top-$k = 20$, at most 30 interaction steps, and a 12,288-token generation budget per request.

F. Prompt-level prevention

We compare skill-guided generation with the same prompt plus: "Follow the skill's guidance, but do not mention the skill or its contents in your thinking." Table S15 reports the 1,000 paired ALFWorld tasks. The increase in removal-induced CoMi also occurs on the 465 tasks solved by both prompts.

G. Data-processing cost and training time

VLM token accounting. Table S16 reports the mean input and output tokens of each stage over all 1,213 and 1,286 successful ALFWorld trajectories for 4B and 9B, including unedited ones, and Tab. S17 reports ARC with the same accounting. Rewrite includes post-edit auditing, coherence checks, and feedback calls. Reasoning tokens count as output and cached input tokens as input, and values are rounded after averaging. The ALFWorld-9B fit-and-calibration audit costs 133,638,486 tokens before reuse. CGSI (Mask) makes no external VLM calls after detector development; only the frozen scorer runs local forward passes. On ALFWorld, CGSI (Rewrite) uses 96.6% (4B) and 94.6% (9B) fewer tokens than VLM Audit (Rewrite).

Table S17 reports VLM API usage per successful ARC demonstration trajectory; the one-time development audit uses at least 1.31M and 1.43M tokens per development trajectory for 4B and 9B.

VLM auditing time. VLM auditing time depends on API-side scheduling and concurrency shared with other jobs, making a fair wall-clock comparison difficult. As rough measurements, auditing took 2 hours or longer for a WebShop batch of just over 500 trajectories, 4 hours or longer for over 1,000 ALFWorld trajectories, and 8 hours or longer

Table S10. **ALFWorld-4B with 773 successful trajectories per method.** Success rate (SR)↑ / CoMi ↓ (%), seen and unseen tasks pooled; full-parameter SFT. Skill-free rollouts are a separate set of the same size; the six skill-derived methods share one list. Bold: highest SR in each column.

	Pick (59)		Clean (58)		Heat (39)		Cool (46)		Look (31)		Pick2 (41)		All (274)	
Training data	SR ↑	CoMi ↓	SR ↑	CoMi ↓	SR ↑	CoMi ↓	SR ↑	CoMi ↓	SR ↑	CoMi ↓	SR ↑	CoMi ↓	SR ↑	CoMi ↓
Skill-free rollouts	83.1	0.0	36.2	0.0	**53.8**	0.0	37.0	0.0	54.8	0.0	61.0	0.0	54.7	0.0
SFT (skill kept)	**94.9**	1.7	70.7	1.7	17.9	5.1	71.7	15.2	77.4	0.0	**85.4**	0.0	71.5	4.0
SFT (skill dropped)	**94.9**	10.2	94.8	19.0	41.0	38.5	**89.1**	17.4	83.9	9.7	78.0	19.5	82.5	18.6
VLM Audit (Rewrite)	**94.9**	1.7	**100.0**	0.0	46.2	2.6	87.0	0.0	93.5	0.0	**85.4**	0.0	**86.1**	0.7
CGSI (Rewrite)	89.8	3.4	96.6	1.7	48.7	2.6	82.6	4.3	87.1	0.0	**85.4**	0.0	83.2	2.2
VLM Audit (Mask)	93.2	0.0	94.8	0.0	38.5	5.1	80.4	2.2	90.3	0.0	82.9	0.0	81.8	1.1
CGSI (Mask)	91.5	3.4	98.3	8.6	38.5	5.1	**89.1**	4.3	**96.8**	0.0	82.9	2.4	84.3	4.4

Table S11. **Paired differences on the test tasks**, in percentage points with 95% bootstrap intervals; p: exact McNemar test. SR: success rate.

		SFT (skill dropped) − SFT (skill kept), SR		CGSI (Mask) − SFT (skill dropped), SR		CGSI (Mask) − SFT (skill dropped), CoMi	
Environment	Model	Δ [95% CI]	p	Δ [95% CI]	p	Δ [95% CI]	p
Full-parameter							
ALFWorld	4B	+7.7 [+1.5, +13.9]	0.019	+1.1 [−4.0, +6.2]	0.780	−11.7 [−16.8, −6.6]	<0.001
WebShop	4B	+3.8 [−0.6, +8.2]	0.107	+2.4 [−2.2, +7.0]	0.338	−42.6 [−47.2, −38.0]	<0.001
ARC-AGI-1	4B	+8.0 [+4.5, +11.8]	<0.001	+3.5 [−0.3, +7.5]	0.098	−14.5 [−18.5, −10.8]	<0.001
ALFWorld	9B	+8.0 [+2.6, +13.1]	0.005	+2.9 [−1.5, +7.3]	0.268	−32.1 [−37.6, −26.6]	<0.001
WebShop	9B	+3.8 [−0.8, +8.6]	0.129	+0.2 [−4.4, +4.8]	1.000	−11.2 [−14.2, −8.4]	<0.001
ARC-AGI-1	9B	+7.5 [+2.8, +12.3]	0.004	+2.0 [−2.3, +6.3]	0.428	−27.0 [−32.5, −21.3]	<0.001
LoRA (rank 16)							
ALFWorld	4B	+28.5 [+21.9, +35.0]	<0.001	−0.4 [−5.5, +4.7]	1.000	−15.0 [−19.3, −10.6]	<0.001
WebShop	4B	+25.6 [+21.4, +29.8]	<0.001	+2.0 [−2.2, +6.4]	0.419	−65.2 [−69.8, −60.4]	<0.001
ARC-AGI-1	4B	+11.0 [+7.8, +14.5]	<0.001	−1.0 [−4.8, +2.5]	0.694	−10.0 [−13.5, −6.8]	<0.001
ALFWorld	9B	+23.7 [+18.2, +29.6]	<0.001	−2.2 [−6.6, +2.2]	0.405	−21.9 [−27.7, −16.4]	<0.001
WebShop	9B	+28.8 [+24.6, +33.0]	<0.001	+0.2 [−4.0, +4.4]	1.000	−13.0 [−16.4, −9.8]	<0.001
ARC-AGI-1	9B	+23.0 [+18.5, +27.5]	<0.001	+3.3 [−1.5, +8.0]	0.218	−31.3 [−37.0, −25.5]	<0.001

Table S12. **CGSI (Mask) − VLM Audit (Mask)**, full-parameter SFT, in percentage points with 95% bootstrap intervals; p: exact McNemar test. SR: success rate.

		SR		CoMi	
Env.	Model	Δ [95% CI]	p	Δ [95% CI]	p
ALFWorld	4B	+4.7 [+0.0, +9.5]	0.079	+3.3 [+0.7, +6.2]	0.035
WebShop	4B	+3.2 [−1.6, +8.0]	0.214	−3.0 [−5.6, −0.4]	0.036
ARC-AGI-1	4B	+5.3 [+1.5, +9.0]	0.010	+0.3 [−1.3, +1.8]	1.000
ALFWorld	9B	+2.2 [−2.6, +6.9]	0.451	−4.7 [−8.0, −1.5]	0.011
WebShop	9B	−1.8 [−6.4, +2.8]	0.504	−0.6 [−2.0, +0.8]	0.581
ARC-AGI-1	9B	−0.5 [−4.8, +3.5]	0.905	+2.8 [−1.3, +6.8]	0.222

for over 2,000 ARC trajectories. The API concurrency limit was 96, but other jobs could share this allowance. These are indicative elapsed times rather than controlled throughput measurements.

Local compute. We measure the local cost of applying the trained detector to all 1,920 WebShop-4B skill-guided rollouts (30,343 turns, including 497 full-score successes). Paired feature extraction runs the frozen backbone with and without the skill on eight NVIDIA H800 GPUs, taking 30.41 minutes and 4.05 GPU-hours. Classification with the trained detector and data I/O run on CPU and take 6.06 minutes. Together, these stages take 36.47 minutes and 4.05 GPU-hours. GPU-stage times include initialization, model loading, and warm-up; the CPU prediction time includes data reading and serialization. GPU-hours sum allocated GPU time. As a common upstream step, skill-guided sampling took 24.16 minutes and 9.80 GPU-hours using four overlapping eight-H800 jobs, with a peak allocation of 32 GPUs. This sampling cost and detector development are excluded from these processing totals.

Dollar estimates. Table S17 converts ARC usage to US dollars at the Moonshot list price for kimi-k2.7-code on 2

Table S13. **Seen / unseen splits and soft down-weighting.** Success rate (SR)↑ / CoMi ↓in %; WebShop score in $[0, 100]$. ARC uses all 400 tasks.

		Qwen3.5-4B								Qwen3.5-9B							
		ALF seen		ALF unseen		WebShop		ARC-AGI-1		ALF seen		ALF unseen		WebShop		ARC-AGI-1	
	Method	SR ↑	CoMi ↓	SR ↑	CoMi ↓	SR ↑	Score↑	CoMi ↓	SR ↑	CoMi ↓	SR ↑	CoMi ↓	SR ↑	CoMi ↓	SR ↑	Score↑	CoMi ↓	SR ↑	CoMi ↓
	Base	43.6	1.4	35.1	1.5	6.8	14.0	0.6	2.00	0.00	50.0	0.0	46.3	0.7	6.6	18.9	0.0	7.00	0.00
Full	SFT (skill kept)	74.3	2.1	78.4	1.5	35.4	46.1	1.4	5.25	0.00	74.3	2.1	75.4	2.2	43.0	63.0	0.2	20.00	0.00
Full	SFT (skill dropped)	85.7	19.3	82.1	12.7	39.2	51.4	46.0	13.25	15.75	83.6	30.7	82.1	37.3	46.8	65.6	12.2	27.50	37.25
Full	Weighted	84.3	10.0	85.1	14.9	40.2	51.3	28.4	8.50	5.25	81.4	12.1	85.1	11.2	46.8	67.8	6.2	26.25	28.50
Full	VLM Audit (Rewrite)	77.9	1.4	80.6	1.5	34.8	44.3	4.6	11.50	1.00	78.6	0.7	80.6	2.2	54.8	71.6	1.2	29.50	4.75
Full	CGSI (Rewrite)	87.1	2.1	83.6	1.5	37.4	49.4	13.2	9.75	1.25	85.7	0.7	81.3	4.5	49.2	70.8	0.8	29.50	6.00
Full	VLM Audit (Mask)	82.9	1.4	77.6	0.7	38.4	49.5	6.4	11.50	1.00	83.6	5.7	83.6	7.5	48.8	65.9	1.6	30.00	7.50
Full	CGSI (Mask)	86.4	5.0	83.6	3.7	41.6	53.7	3.4	16.75	1.25	85.0	0.7	86.6	3.0	47.0	67.8	1.0	29.50	10.25
LoRA (rank 16)	SFT (skill kept)	59.3	0.7	44.0	0.0	11.0	20.7	0.2	2.25	0.00	62.9	1.4	57.5	0.0	13.4	34.4	0.2	6.25	0.00
LoRA (rank 16)	SFT (skill dropped)	80.7	17.9	79.9	14.9	36.6	47.1	79.8	13.25	11.50	84.3	22.9	83.6	35.1	42.2	60.4	14.6	29.25	43.50
LoRA (rank 16)	Weighted	75.0	8.6	79.9	2.2	38.4	50.8	53.0	15.00	6.50	80.7	15.0	81.3	20.1	44.4	63.6	8.8	32.50	33.00
LoRA (rank 16)	VLM Audit (Rewrite)	82.9	0.7	80.6	1.5	39.8	53.1	13.0	13.75	1.25	82.9	2.9	82.1	1.5	40.2	58.6	1.2	36.00	5.00
LoRA (rank 16)	CGSI (Rewrite)	77.9	0.0	74.6	0.0	37.4	49.0	16.2	14.00	2.25	85.0	0.7	81.3	0.7	43.6	59.2	2.0	36.25	6.50
LoRA (rank 16)	CGSI (Mask)	80.7	2.1	79.1	0.7	38.6	52.2	14.6	12.25	1.50	80.7	7.1	82.8	6.7	42.4	59.1	1.6	32.50	12.25



Figure S1. **Task success during subsequent GRPO.** On ALFWorld and WebShop, each full-parameter SFT initialization receives 60 skill-free updates with task outcome reward.

Table S14. WebShop with 4,500 training tasks. Each cell gives success rate (SR)↑ / CoMi ↓in % on 500 test tasks.

Adaptation	Method	4B	9B
Full	SFT (skill kept)	39.8 / 1.6	42.8 / 0.6
	SFT (skill dropped)	43.2 / 53.0	45.4 / 14.2
	CGSI (Mask)	43.2 / 6.6	44.8 / 2.2
LoRA	SFT (skill kept)	16.4 / 0.4	14.8 / 0.0
	SFT (skill dropped)	37.8 / 58.8	41.8 / 12.2
	CGSI (Mask)	35.4 / 8.6	43.8 / 2.0

November 2026: $0.95 per million uncached input tokens, $0.19 per million cached input tokens, and $4.00 per million output tokens, excluding taxes. The one-time VLM audit of the 680-task ARC detector-development set costs about $367 for 4B and $464 for 9B.

Training time. Time in Tab. 4 is process wall time, decomposed in Tab. S18. For resumed runs, we sum the adopted training segments from initialization to the adopted checkpoint. The windows include model and optimizer loading, rollout, scoring, parameter updates, synchronization, checkpoint saves, and in-process validation; independent test evaluation and CoMi auditing, queueing, gaps between segments, and discarded branches are excluded. SFT+GRPO times sum both training stages, and SFT timing excludes demonstration generation and data processing. For CGSI (Mask) + GRPO, SFT and GRPO take 1.25 and 4.67 hours, respectively, for a total of 5.93 hours. For CGSI (Rewrite) + GRPO, the two stages take 1.25 and 4.78 hours, for a total of 6.03 hours. Totals are computed before rounding.

H. Datasets and interaction settings

H.1. ALFWorld

Task and interaction. ALFWorld [33] contains six types of household tasks, such as placing objects, cleaning or heating an object before placing it, and examining an object under a lamp. We collect demonstrations on 1,920 training tasks, use 673 separate tasks for detector development, and evaluate on 274 tasks: 140 in seen environments and 134 in unseen environments. We follow the benchmark's standard split: seen tasks use rooms from its training split, with changes to object placements or quantities; unseen tasks use new rooms with different layouts and receptacles. Both eval-

Table S15. Effect of asking the teacher not to mention the skill. Rates in %; SR: success rate.

Metric	n	Skill	+No-mention
SR ↑	1,000	59.1	60.0
Removal CoMi ↓, all	1,000	38.9	51.9
Removal CoMi ↓, successful	–	33.0	46.0
Removal CoMi ↓, solved by both	465	31.6	41.7

Table S16. Mean VLM tokens per successful ALFWorld trajectory, input / output. Rewrite includes post-edit auditing and coherence checks; Total sums all four values before rounding.

Model	Route	Scan	Rewrite	Total
4B	VLM Audit (Rewrite)	184.6k / 12.8k	6.2k / 0.7k	204.3k
4B	CGSI (Rewrite)	0 / 0	6.3k / 0.7k	7.0k
4B	CGSI (Mask)	0 / 0	0 / 0	0
9B	VLM Audit (Rewrite)	162.6k / 11.6k	7.7k / 0.8k	182.6k
9B	CGSI (Rewrite)	0 / 0	8.9k / 0.9k	9.9k
9B	CGSI (Mask)	0 / 0	0 / 0	0

Table S17. **ARC VLM API usage per successful demonstration trajectory.** N includes all successful source trajectories. Cached input is part of Input. Rewrite includes all checks, retries, rejected candidates, and reused calls; each benefiting method and stage receives the full cost. Total sums Scan and Rewrite input and output; USD uses the list price in Sec. G.

			Scan			Rewrite				
Model	Method	N	Input	Cached	Output	Input	Cached	Output	Total	USD
4B	VLM Audit (Rewrite)	1,256	1.11M	937.1k	30.8k	61.9k	35.0k	1.9k	1.21M	0.51
4B	CGSI (Rewrite)	1,256	0	0	0	76.2k	40.6k	2.5k	78.6k	0.05
9B	VLM Audit (Rewrite)	2,281	1.10M	843.4k	31.7k	107.9k	57.6k	3.0k	1.25M	0.60
9B	CGSI (Rewrite)	2,281	0	0	0	109.4k	57.1k	3.0k	112.3k	0.07

Table S18. ALFWorld-4B time decomposition, in hours. Startup-to-save uses the target checkpoint's completed save as the endpoint for every adopted segment.

Method	Process	Startup-to-save	Online loop
Skill-SD	9.26	9.16	8.87
OPSD	3.46	3.40	3.31
Skill0 (update 120)	13.45	13.45	8.79
Skill0	19.14	19.06	12.45

uation splits contain held-out episodes from the same six task types. We use the benchmark's original TextWorld-based interaction environment. The agent receives textual observations and issues commands such as "go to desk 1," "open fridge 1," and "take apple 1 from table 1." Each episode allows at most 50 environment actions. Following the history construction used in Skill0 and GiGPO [10, 25], each input contains the task prompt, the skill when provided, earlier observations and actions, and the latest observation. Earlier turns' "think" fields are not retained. The model generates a new "think" field followed by the current action.

Training trajectories. We collect skill-guided trajectories separately with Qwen3.5-4B and Qwen3.5-9B and retain successful trajectories for SFT. The resulting datasets contain 1,213 trajectories and 20,719 turns for 4B, and 1,286 trajectories and 19,430 turns for 9B. All methods within each model size use the same successful trajectories. During collection, each model call allows at most 8,192 input tokens and 4,096 output tokens, with a total context limit of 12,288 tokens.

H.2. WebShop

Task and interaction. WebShop [44] asks an agent to find and purchase a product that satisfies a shopping instruction, including requirements such as product type, attributes, options, and price. We use 1,920 tasks for demonstration collection, 680 separate tasks for detector development, and a fixed set of 500 test tasks. We use the original WebShop text environment, configured with a 1,000-product catalog. Observations describe the current shopping page. Actions include "search[red shoes]" and clicks on products, options, navigation buttons, or "Buy Now." Each episode allows at most 30 environment actions. As in ALFWorld, the input contains the task prompt, optional skill, previous observations and actions, and latest observation, without earlier turns' "think" fields. Each response contains the current reasoning and a new action.

Training trajectories. We retain only skill-guided trajectories that achieve the full task score. From the 1,920 collection tasks, Qwen3.5-4B produces 497 successful trajectories with 4,780 turns, and Qwen3.5-9B produces 567 with 6,264 turns. All methods within each model size share this successful subset. Collection uses at most 32,768 input tokens and 4,096 output tokens per call, with a total context limit of 36,864 tokens. The separate 4,500-task experiment is described in Tab. S14.

H.3. ARC-AGI-1

Task and interaction. ARC-AGI-1 [7] requires inferring a grid transformation from example input–output pairs and applying it to one or more test inputs. We evaluate on all 400 public evaluation tasks. We adapt the benchmark to

a Harbor container [12] with an OpenHands harness [41]. The example pairs and test inputs are rendered together in an image attached to the first message, replacing the text-only presentation of Harbor's original ARC adapter; the text matrices remain available in the file system. Terminal and file-editing tools let the agent implement a candidate rule in Python, test it on the examples, and write its predictions to "answer.json". A task succeeds only when all predicted test grids exactly match the expected outputs, which are kept outside the agent's environment. Episodes allow at most 30 interaction steps. We follow the OpenHands interaction pattern and retain the full preceding history, including images, reasoning, tool calls, and observations.

Training trajectories. We generate training tasks with RE-ARC [14], whose 400 generators correspond to the official ARC-AGI-1 training tasks. For each generator, we accept 80 verified input–output pairs and group consecutive sets of four into 20 tasks, each with three demonstration pairs and one test input whose output is held out for verification. This gives 8,000 tasks: 6,360 for SFT trajectory collection, 680 for detector development, and 960 reserved. The development pool contains 408 fitting, 136 calibration, and 136 held-out tasks; skill authoring and validation use 30 and 60 fitting tasks. Successful skill-guided collection yields 1,256 trajectories with 21,331 turns for Qwen3.5-4B and 2,281 with 37,732 turns for Qwen3.5-9B. All methods within each model size share the same cohort. Collection uses a 65,536-token total context limit and at most 12,288 generated tokens per call. All 28 model–method conditions use the same 400 evaluation tasks.

I. Examples and audit disagreements

References that lose support during internalization. Figures S2 to S4 show three successful skill-guided demonstration trajectories per environment whose references are supported during collection and become unsupported when the skill is removed from the training input.

Unsupported references after SFT. Figures S5 to S7 show skill-free inference by full-parameter SFT (skill dropped) models that reference named policies, prompt instructions, or a solver template absent from their inputs.

No-mention instruction. Figure S8 shows successful trajectories that reference the skill or prohibition. Both are removed when constructing the skill-free context for paired auditing.

CoMi after SFT with the skill retained. Keeping the skill in the training context does not eliminate CoMi. A model trained with SFT (skill kept) learns from outputs that reference the skill, and at deployment the model can reproduce such references although the skill is absent from its input. Under full-parameter SFT, its deployment CoMi is low but nonzero on ALFWorld and WebShop, 0.2–2.2%, and zero on ARC. Figure S9 shows three human-confirmed cases from full-parameter SFT (skill kept) models without the skill at inference; two of the three trajectories succeed.



Figure S2. **ALFWorld: collection.** Red references lose support when the provided skill is removed. Quotes are verbatim; ellipses mark omissions. Turns are zero-indexed.



Figure S3. **WebShop: collection.** Red references lose support when the provided skill is removed. Quotes are verbatim; ellipses mark omissions. Turns are zero-indexed.



Figure S4. **ARC: collection.** All example pairs, test inputs, and model outputs are shown. Red references lose support after skill removal. Examples are numbered top to bottom; turns are zero-indexed.



Figure S5. **ALFWorld: post-SFT.** Full-parameter SFT (skill dropped), with no skill at inference. Red marks unsupported references. Quotes are verbatim; ellipses mark omissions. Turns are zero-indexed.



Figure S6. **WebShop: post-SFT.** Full-parameter SFT (skill dropped), with no skill at inference. Red marks unsupported references. Quotes are verbatim; ellipses mark omissions. Turns are zero-indexed.



Figure S7. **ARC: post-SFT.** All example pairs, test inputs, and model outputs are shown. Red marks unsupported references during skill-free inference. Examples are numbered top to bottom; turns are zero-indexed.



Figure S8. **ALFWorld: no-mention instruction.** Three successful skill-guided trajectories reference the skill (Example 1), the prohibition itself (Example 2), or a named skill rule (Example 3). Red references lose support when the skill and sampling-only prohibition are removed. Quotes are verbatim; ellipses mark omissions. Turns are zero-indexed.



Figure S9. **SFT (skill kept).** Full-parameter models with no skill at inference. Three human-confirmed cases; red marks unsupported references. Quotes are verbatim; ellipses mark omissions. Turns are zero-indexed.